

CMKD6001

**SURFACE MOUNT
TRIPLE ISOLATED
ULTRA LOW LEAKAGE
SILICON SWITCHING DIODES**



www.centrasemi.com

ULTRAmTMini



SOT-363 CASE

DESCRIPTION:

The CENTRAL SEMICONDUCTOR CMKD6001 type contains three (3) Isolated Silicon Switching Diodes, manufactured by the epitaxial planar process, epoxy molded in a ULTRAmTMini surface mount package, designed for switching applications requiring extremely low leakage.

MARKING CODE: K01

MAXIMUM RATINGS: (T_A=25°C)

Continuous Reverse Voltage
Peak Repetitive Reverse Voltage
Continuous Forward Current
Peak Repetitive Forward Current
Peak Forward Surge Current, t_p=1.0μs
Peak Forward Surge Current, t_p=1.0s
Power Dissipation
Operating and Storage Junction Temperature
Thermal Resistance

SYMBOL

V_R 75
V_{RRM} 100
I_F 250
I_{FRM} 500
I_{FSM} 4.0
I_{FSM} 1.0
P_D 250
T_J, T_{stg} -65 to +150
θ_{JA} 500

UNITS

V
V
mA
mA
A
A
mW
°C
°C/W


ELECTRICAL CHARACTERISTICS PER DIODE: (T_A=25°C unless otherwise noted)

| SYMBOL | TEST CONDITIONS | MIN | MAX | UNITS |
|-----------------|--|-----|------|-------|
| I _R | V _R =75V | | 500 | pA |
| BV _R | I _R =100μA | 100 | | V |
| V _F | I _F =1.0mA | | 0.85 | V |
| V _F | I _F =10mA | | 0.95 | V |
| V _F | I _F =100mA | | 1.1 | V |
| C _T | V _R =0, f=1.0MHz | | 2.0 | pF |
| t _{rr} | I _R =I _F =10mA, I _{rr} =1.0mA, R _L =100Ω | | 3.0 | μs |


CMKD6001
SURFACE MOUNT
TRIPLE ISOLATED
ULTRA LOW LEAKAGE
SILICON SWITCHING DIODES



SOT-363 CASE - MECHANICAL OUTLINE



PIN CONFIGURATION



| SYMBOL | INCHES | | MILLIMETERS | |
|--------|--------|-------|-------------|------|
| | MIN | MAX | MIN | MAX |
| A | 0.004 | 0.010 | 0.10 | 0.25 |
| B | 0.005 | - | 0.12 | - |
| C | 0.000 | 0.004 | 0.00 | 0.10 |
| D | 0.031 | 0.043 | 0.80 | 1.10 |
| E | 0.071 | 0.087 | 1.80 | 2.20 |
| F | 0.051 | | 1.30 | |
| G | 0.026 | | 0.65 | |
| H | 0.075 | 0.091 | 1.90 | 2.30 |
| J | 0.043 | 0.055 | 1.10 | 1.40 |
| K | 0.006 | 0.012 | 0.15 | 0.30 |

SOT-363 (REV: R2)

LEAD CODE:

- 1) Anode D1
- 2) Anode D2
- 3) Anode D3
- 4) Cathode D3
- 5) Cathode D2
- 6) Cathode D1

MARKING CODE: K01

R5 (9-May 2011)