

CMLTA44

**SURFACE MOUNT
EXTREMELY HIGH VOLTAGE
NPN SILICON TRANSISTOR**



www.centrasemi.com

PICOmini™



SOT-563 CASE

DESCRIPTION:

The CENTRAL SEMICONDUCTOR CMLTA44 type is an NPN High Voltage transistor, epoxy molded in a space saving PICOmini™ SOT-563 surface mount package and designed for extremely high voltage applications.

MARKING CODE: 44C

MAXIMUM RATINGS: ($T_A=25^\circ\text{C}$)

Collector-Base Voltage
Collector-Emitter Voltage
Emitter-Base Voltage
Continuous Collector Current
Power Dissipation
Operating and Storage Junction Temperature
Thermal Resistance

SYMBOL

V_{CBO}	450
V_{CEO}	400
V_{EBO}	6.0
I_C	300
P_D	250
T_J, T_{stg}	-65 to +150
θ_{JA}	500

UNITS

V
V
V
mA
mW
°C
°C/W

ELECTRICAL CHARACTERISTICS: ($T_A=25^\circ\text{C}$ unless otherwise noted)



SYMBOL	TEST CONDITIONS	MIN	MAX	UNITS
I_{CBO}	$V_{CB}=400V$		100	nA
I_{CES}	$V_{CE}=400V$		500	nA
I_{EBO}	$V_{EB}=4.0V$		100	nA
BV_{CBO}	$I_C=100\mu A$	450		V
BV_{CES}	$I_C=100\mu A$	450		V
BV_{CEO}	$I_C=1.0mA$	400		V
BV_{EBO}	$I_E=10\mu A$	6.0		V
$V_{CE(SAT)}$	$I_C=1.0mA, I_B=0.1mA$		0.40	V
$V_{CE(SAT)}$	$I_C=10mA, I_B=1.0mA$		0.50	V
$V_{CE(SAT)}$	$I_C=50mA, I_B=5.0mA$		0.75	V
$V_{BE(SAT)}$	$I_C=10mA, I_B=1.0mA$		0.75	V
h_{FE}	$V_{CE}=10V, I_C=1.0mA$	40		
h_{FE}	$V_{CE}=10V, I_C=10mA$	50	200	
h_{FE}	$V_{CE}=10V, I_C=50mA$	45		
h_{FE}	$V_{CE}=10V, I_C=100mA$	20		
f_T	$V_{CE}=10V, I_C=10mA, f=10MHz$	20		MHz
C_{ob}	$V_{CB}=20V, I_E=0, f=1.0MHz$		7.0	pF
C_{ib}	$V_{EB}=0.5V, I_C=0, f=1.0MHz$		130	pF

R1 (20-January 2010)

CMLTA44
SURFACE MOUNT
EXTREMELY HIGH VOLTAGE
NPN SILICON TRANSISTOR



SOT-563 CASE - MECHANICAL OUTLINE



SYMBOL	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.004	0.007	0.10	0.18
B	0.008		0.20	
C	0.022	0.024	0.56	0.60
D	0.059	0.067	1.50	1.70
E	0.020		0.50	
F	0.061	0.067	1.55	1.70
G	0.047		1.20	
H	0.006	0.012	0.15	0.30

SOT-563 (REV: R0)

LEAD CODE:

- 1) Collector
 - 2) Collector
 - 3) Base
 - 4) Emitter
 - 5) Collector
 - 6) Collector
- Pins 1, 2, 5 and 6 are common.

MARKING CODE: 44C

R1 (20-January 2010)