


### 1808 SMT Capacitors feature:

- 1808 Case Size
- High Voltage
- High Capacitance
- X7R Dielectric Material

### Mechanical Dimensions



Length (L): .180" ± .010"

Width (W): .080" ± .010"

Thickness (T): .080" max

Bandwidth (bw): .030"

### Capacitance Value

Value (pF)	Cap. Code	Max Voltage	Dielectric	Value (pF)	Cap. Code	Max Voltage	Dielectric
100	101	3000 VDC	X7R	22,000 (.022μF)	223	1000 VDC	X7R
150	151		X7R	27,000 (.027μF)	273		X7R
220	221		X7R	33,000 (.033μF)	333	↓	X7R
330	331		X7R	39,000 (.039μF)	393	500 VDC	X7R
470	471		X7R	47,000 (.047μF)	473	↓	X7R
680	681		X7R	56,000 (.056μF)	563	↓	X7R
820	821		X7R	68,000 (.068μF)	683	300 VDC	X7R
1000	102		X7R	82,000 (.082μF)	823	↓	X7R
1500	152		X7R	100,000 (.10μF)	104	200 VDC	X7R
1800	182		X7R				
2200	222		X7R				
2700	272		X7R				
3300	332	↓	X7R				
3900	392	2000 VDC	X7R				
4700	472		X7R				
5600	562		X7R				
6800	682		X7R				
8200	822		X7R				
10,000 (.01μF)	103	↓	X7R				
15,000 (.015μF)	153	1000 VDC	X7R				
18,000 (.018μF)	183	↓	X7R				

**\*\* For Additional Capacitance Values and Working Voltages, Please Contact the Factory \*\***

### ORDERING INFORMATION

Case Size	Dielectric	Capacitance	Tolerance	Voltage	Termination	Packaging	Hi-Reli Testing
1808	X	822	K	202	SN	T	- A
Mechanical Dimensions Shown Above	X = X7R	First 2 digits are Significant; Third digit indicates # of Zeros. Use "R" for decimal point Examples: 201 = 200pF 226 = 22μF	D ± 0.5pF F ±1% G ±2% J ±5% K ±10% M ±20%	First 2 digits are Significant; Third digit indicates number of Zeros Examples: 201 = 200V 151 = 150V 202 = 2000V	S Solder Plated Over Nickel SN Tin over Nickel Plated (RoHS Compliant) G Gold over Nickel Plated (RoHS Compliant)	T = Tape and Reel W = Waffle Pack	(Optional) A = Group A B = Group B C = Group C Tested and Screened