

ASSP For Screen Display Control

CMOS

On-Screen Display Controller

MB90050

■ DESCRIPTION

The MB90050 is an on-screen display controller for displaying text and graphics on the TV screen.

The MB90050 controls a display area of 35 characters by 16 lines, and provides each character composed of 24×32 dots at most. The display functions include a wealth of characters with qualifying functions such as character background shading (shadow casting), sprite character functions and graphic character functions, contributing to the use of control GUI displays. The MB90050 incorporates display memory (VRAM), character font ROM, and sync signal generation circuit and video signal generation circuit supporting the NTSC and PAL systems, allowing text and graphics to be displayed in conjunction with a small number of external components.


■ FEATURES

- Main screen display capacity
35 characters \times 16 lines (maximum 560 characters)
- Character configuration
Normal characters : 24×32 dots
Graphic characters : 12×16 dots* (colorable per 1 dot)

(Continued)

■ PACKAGE

48-pin plastic QFP



(FPT-48P-M15)

MB90050

- Font display configuration
 - Three horizontal width settings (selectable setting L/M/S for each character) per character.
 - L size : 24 dots
 - M size : 18 dots
 - S size : 12 dots
 - Two vertical height settings (selectable A/B for each line) per line.
 - A : 18 to 32 dots (setting per 2 dots)
 - B : 18 to 32 dots (setting per 2 dots)
 - (These sizes are dot sizes of typical character. Each size of graphic characters uses half the number of dots of typical characters. Note, however, that both of the typical and graphic characters are the same in character area size.)
- Character types
 - Usable all 512 character types (font ROM+, font RAM)
 - Font ROM : 512 character types (all area user setting)
 - Font RAM : 8 character types (all area user command setting)
 - Capable of setting a specific eight-character area in font ROM so that the area is replaced with font RAM.
- Display modes
 - Character : Normal character/graphic character (set for each character)
 - Character trimming : Side trimming 1/side trimming 2/patern background 1/patern background 2 (set for each screen)
 - Character background : None/Solid-fill/Shaded background (concave) /Shaded background (convex) (set for each character)
 - Line background : None/Solid-fill/Shaded background (concave) /Shaded background (convex) (set for each line)
 - Character enlargement : Normal, Double width, Double height, Double width × double height (set for each line)
 - Brink : OFF/ON (set for each character)
- Main screen display position control
 - Horizontal display position : Control in 2-dot units (movable through the entire screen)
 - Vertical display position : Control in 2-dot units (movable through the entire screen)
 - Line spacing control : 0 to 14 dots, 2-dot units (set for each line)
 - Sprite character display control
 - Capable of displaying one block for an arbitrary character on the topmost layer on the screen.
 - Sprite character display : OFF/ON (graphic character display)
 - Sprite character types : 256 types (character codes 000_H to 0FF_H)
 - Sprite character configuration : 1 character/2 characters horizontal/2 characters vertical/2×2 characters
 - Sprite character horizontal display position : Control in 1-dot units
 - Sprite character vertical display position : Control in 1-dot units
 - Screen background color display control
 - Capable of displaying an arbitrary color on the entire bottommost layer on the screen.
 - Screen background color display : OFF/ON
- Display colors
 - Digital output : 16 colors selectable from among 64 colors (built in palette circuit)
 - Video output : Any 16 colors selectable (Command setting enable)

(Continued)


(Continued)

- Display colors and setting units
 - Character color : 16 colors (set for each character)
 - Character background color : 16 colors (set for each character)
 - Character trimming color : 16 colors (set for each line)
 - Line background color : 16 colors (set for each line)
 - Graphic character color : 16 colors (set for each dot)
 - Sprite character color : 16 colors (set for each dot)
 - Screen background character color : 16 colors (set for each dot)
 - Screen background color : 16 colors (set for all screen)
 - Shaded background frame highlight color : 16 colors (set for all screen)
 - Shaded background frame shadow color : 16 colors (set for all screen)
- Digital display signal output
 - Color signal output : DCOL5 to DCOL0 pins (6 bits)
 - Display period signal output : DB pin
 - Translucent display period signal output : DH pin
- Analog (video) signal input/output
 - Composit video input/output : VIN, VOUT pins
 - Y/C video input/output : YIN, YOUT pins, CIN, COUT pins
- Internal sync control
 - Internal sync signal generator and video signal generator supporting the NTSC and PAL systems.
- External interface
 - 16-bit serial input (3-signal input)
 - Chip select signal
 - Serial clock signal
 - Serial data signal
- Package
 - QFP-48P (FPT-48P-M15)
- Supply voltage
 - +5 V \pm 10%

* : 1 dot of graphic characters is the same size as 2 \times 2 dots of normal characters.

MB90050

■ PIN ASSIGNMENT



■ PIN DESCRIPTIONS

Pin no.	Pin name	I/O	Circuit type	Function
6, 7	EXS, XS	I/O	A	Crystal oscillation circuit pins for color burst clock generator. Connect an external crystal oscillator (14.31818 MHz for NTSC or 17.734475 MHz for PAL) and load capacitance (C) to these pins to form a crystal oscillation circuit.
20, 19	EXD, XD	I/O	B	LC oscillation circuit pins for display dot clock generator. Connect these pins to external "L" and "C" to form an LC oscillation circuit.
15	\overline{CS}	I	C	Chip select signal input pin. For serial command transfer, set this pin to the Low level.
16	SCLK	I	C	Serial clock signal input pin. This pin feeds a clock signal upon transfer of a serial command. It feeds serial data at the rising edge.
17	SIN	I	C	Serial data signal input pin. Input data during serial command transfer.
18	BUSY	O	F	Busy signal output pin. This pin outputs a significant level signal during VRAM filling. Do not input a serial command while the pin outputs the significant level signal. Supplying a low level signal to the \overline{CS} pin during the significant level signal output period terminates the VRAM fill operation and causes this pin to output an insignificant level signal. The pin enables output (ON/OFF) control, output logic control, and internal pull-up ON/OFF control depending on the command setting. When the \overline{RESET} pin inputs a low level signal, this pin outputs the busy signal, turns off the internal pull-up resistor, and sets the output to OFF (output tied to the low).
2	\overline{VSYNCI}	I	D	Vertical sync signal input pin. Active low signal or active high signal input is command-selectable for the pin. When the \overline{RESET} pin inputs the low level signal, this pin inputs the active low signal.
3	\overline{HSYNCI}	I	D	Horizontal sync signal input pin. Active low signal or active high signal input is command-selectable for the pin. When the \overline{RESET} pin inputs the low level signal, this pin inputs the active low, horizontal sync signal.
1	FLDI	I	D	Field signal input pin. The internal field signal identically detected from among input sync signals or the input signal to this pin is command-selectable for field control. During operation under external synchronization control, the input signal is used to control the least significant bit of the font ROM/RAM raster address. The input signal to this pin is disabled during operation under internal synchronization control.

(Continued)

Pin no.	Pin name	I/O	Circuit type	Function
9	$\overline{\text{VSYNCO}}$	O	F	Vertical sync signal output pin. The pin enables output (ON/OFF) control, output logic control, and internal pull-up ON/OFF control depending on the command setting. When the $\overline{\text{RESET}}$ pin inputs the low level signal, this pin turns off the internal pull-up resistor and sets the output to OFF (output tied to the high).
10	$\overline{\text{HSYNCO}}$	O	F	Horizontal sync signal output pin. The pin enables output (ON/OFF) control, output logic control, and internal pull-up ON/OFF control depending on the command setting. When the $\overline{\text{RESET}}$ pin inputs the low level signal, this pin turns off the internal pull-up resistor and sets the output to OFF (output tied to the high).
11	$\overline{\text{CSYNCO}}$	O	F	Composite sync signal output pin. The pin enables output (ON/OFF) control, output logic control, and internal pull-up ON/OFF control depending on the command setting. When the $\overline{\text{RESET}}$ pin inputs the low level signal, this pin turns off the internal pull-up resistor and sets the output to OFF (output tied to the high).
12	VBLKO	O	F	Vertical blanking interval (VBI) output pin. The pin enables output (ON/OFF) control, output logic control, and internal pull-up ON/OFF control depending on the command setting. When the $\overline{\text{RESET}}$ pin inputs the low level signal, this pin turns off the internal pull-up resistor and sets the output to OFF (output tied to the low).
13	FLDO	O	F	Field signal output pin. During operation under internal synchronization control, this pin outputs the internally generated field signal. During operation under external synchronization control, the pin outputs the field signal (internally detected field signal or external input field signal) used for internal operations. The pin enables output (ON/OFF) control, output logic control, and internal pull-up ON/OFF control depending on the command setting. When the $\overline{\text{RESET}}$ pin inputs the low level signal, this pin turns off the internal pull-up resistor and sets the output to OFF (output tied to the low).
14	SYNCST	O	F	Synchronization detection signal output pin. This pin outputs a significant level signal with a sync signal detected and an insignificant level signal with no sync signal detected. The pin enables output (ON/OFF) control, output logic control, and internal pull-up ON/OFF control depending on the command setting. When the $\overline{\text{RESET}}$ pin inputs the low level signal, this pin turns off the internal pull-up resistor and sets the output to OFF (output tied to the low).

(Continued)

Pin no.	Pin name	I/O	Circuit type	Function
28	DCLKO	O	G	<p>Dot clock signal output pin. This pin outputs an LC oscillation clock signal. The pin enables output (ON/OFF) control depending on the command setting. The normal clock (that stops oscillation during horizontal synchronization) or continuous clock (that does not stop oscillation during horizontal synchronization*) can be command-selected for the output using the command setting for output selection control (CKS). When the $\overline{\text{TESTI2}}$ pin inputs a low level signal, this pin outputs the continuous clock signal that does not stop oscillation during horizontal synchronization (where the output selection control (CKS) setting is disabled). When the $\overline{\text{RESET}}$ pin inputs the low level signal, the pin outputs a dot clock signal. * : For continuous clock, this pin is used for frequency measurement. To measure the dot clock, the pin sets display signal output that is not the standard and cannot display correctly.</p>
8	FSC40	O	G	<p>Crystal oscillator 4FSC clock signal output pin. This pin enables output (ON/OFF) control depending on the command setting. The crystal oscillation clock (4FSC) or its 1/4 frequency clock (FSC) can be command-selected for the output using the command setting for output selection control (FSS). When the $\overline{\text{TESTI2}}$ pin inputs the low level signal, this pin outputs the 4FSC clock signal (where the output selection control (FSS) setting is disabled). When the $\overline{\text{RESET}}$ pin inputs the low level signal, this pin outputs the 4FSC clock signal.</p>
26	DH	O (I)	H	<p>Halftone display period signal output pin. This pin enables output (ON/OFF) control and output logic control depending on the command setting. When the $\overline{\text{RESET}}$ pin inputs the low level signal, this pin sets the output to OFF (output tied to the low). (The input feature of the pin is a test function. Use the pin usually only for output.)</p>
27	DB	O (I)	H	<p>Display period signal output pin. This pin enables output (ON/OFF) control and output logic control depending on the command setting. When the $\overline{\text{RESET}}$ pin inputs the low level signal, this pin sets the output to OFF (entering the low level signal fixed output state). (The input feature of the pin is a test function. Use the pin usually only for output.)</p>
34, 33, 32, 31, 30, 29	DCOL5, DCOL4, DCOL3, DCOL2, DCOL1, DCOL0	O (I)	H	<p>Display color signal output pin. This pin enables output (ON/OFF) control and output logic control depending on the command setting. When the $\overline{\text{RESET}}$ pin inputs the low level signal, this pin sets the output to OFF (entering the low level signal fixed output state). (The input feature of the pin is a test function. Use the pin usually only for output.)</p>
36, 35, 24, 23	PO3, PO2, PO1, PO0	O (I)	H	<p>Port signal output pin. This pin enables output level (High/Low) control depending on the command setting. When the $\overline{\text{RESET}}$ pin inputs the low level signal, this pin sets the output to OFF (entering the low level signal fixed output state). (The input feature of the pin is a test function. Use the pin usually only for output.)</p>





(Continued)

MB90050

(Continued)

Pin no.	Pin name	I/O	Circuit type	Function
25	$\overline{\text{RESET}}$	I	C	Reset signal input pin. Upon input of the low level signal, this pin causes an internal reset. After the power supply is inserted, the reset input is required for normal operation. During regular operation, the pin inputs the high level signal.
37	$\overline{\text{TESTI1}}$	I	E	Test signal input pin. Input High level signal during normal operation. (Input of the Low level signal activates test mode operation.)
47	$\overline{\text{TESTI2}}$	I	E	Test signal input pin. Input High level signal during normal operation.
38	VIN	I	I	Composite video signal input pin. This pin inputs a DC-reproduced signal of 2 V _{P-P} (pedestal level 1.57 V, sync tip level 1 V) .
46	YIN	I	I	Luminance video signal (Y video signal) input pin. This pin inputs a DC-reproduced signal of 2 V _{P-P} (pedestal level 1.57 V, sync tip level 1 V) .
44	CIN	I	I	Saturation video signal (C video signal) input pin. This pin inputs a signal at 1.57 VDC and a color burst signal amplitude of 0.57 V _{P-P} .
40	VOUT	O	I	Composite video signal output pin. This pin outputs a signal of 2 V _{P-P} (pedestal level 1.57 V, sync tip level 1 V) . When the $\overline{\text{RESET}}$ signal inputs the low level signal, this pin outputs the black video (pedestal level without color burst) signal.
48	YOUT	O	I	Luminance video signal (Y video signal) output pin. This pin outputs a signal of 2 V _{P-P} (pedestal level 1.57 V, sync tip level 1 V) . When the $\overline{\text{RESET}}$ pin inputs the low level signal, this pin outputs the black video (pedestal level) signal.
42	COUT	O	I	Saturation video signal (C video signal) output pin. This pin outputs a signal at 1.57 VDC and a color burst signal amplitude of 0.57 V _{P-P} . When the $\overline{\text{RESET}}$ pin inputs the low level signal, this pin outputs the black video signal (a DC voltage of 1.57 V without color burst).
4, 22	V _{CC}	—	—	Power supply pin for digital circuit. These pins supply +5 V and make all V _{CC} pins same potential.
5, 21	V _{SS}	—	—	Digital ground pins. These pins make all V _{SS} pins and AV _{SS1} /AV _{SS2} pins same potential.
39	AV _{CC1}	—	—	Power supply pin for analog circuit and composite video signal Input/Output (VIN-VOUT) circuit. This pin supplies +5 V. Input analog ground level when not using this analog circuit.
43	AV _{CC2}	—	—	Power supply pin for analog circuit, luminance video signal Input/Output (YIN-YOUT) circuit, and saturation video signal Input/Output (CIN-COUT) circuit. This pin supplies +5 V. Input analog ground level when not using this analog circuit.
41, 45	AV _{SS1} , AV _{SS2}	—	—	Analog ground pins. AV _{SS1} pin makes AV _{SS2} pin same potential. V _{SS} pins make these pins same potential.

■ I/O CIRCUIT TYPES

Type	Circuit	Remarks
A		<ul style="list-style-type: none"> • Crystal oscillation • Oscillator feedback resistor (approx. 1MΩ)
B		<ul style="list-style-type: none"> • LC oscillation
C		<ul style="list-style-type: none"> • TTL level, Hysteresis input
D		<ul style="list-style-type: none"> • CMOS level, Hysteresis input
E		<ul style="list-style-type: none"> • CMOS level, Hysteresis input with pull-up resistor (approx. 50 kΩ)


(Continued)

MB90050

(Continued)

Type	Circuit	Remarks
F		<ul style="list-style-type: none"> Nch open-drain output with pull-up resistor SW (approx. 50 kΩ)
G		<ul style="list-style-type: none"> CMOS output
H		<ul style="list-style-type: none"> CMOS I/O Input is for test.
I		<ul style="list-style-type: none"> Analog I/O CMOS analog SW

■ BLOCK DIAGRAM



■ ABSOLUTE MAXIMUM RATINGS

Parameter	Symbol	Rating		Unit	Remarks
		Min	Max		
Power supply voltage*1	V _{CC}	V _{SS} - 0.5	V _{SS} + 7.0	V	*2
	AV _{CC1}	V _{SS} - 0.5	V _{SS} + 7.0	V	*2
	AV _{CC2}	V _{SS} - 0.5	V _{SS} + 7.0	V	*2
Input voltage*1	V _{IN}	V _{SS} - 0.5	V _{CC} + 0.5	V	
Output voltage*1	V _{OUT}	V _{SS} - 0.5	V _{CC} + 0.5	V	
“L” level maximum output current	I _{OL}	—	15	mA	
“H” level maximum output current	I _{OH}	—	-15	mA	
Power consumption	P _d	—	500	mW	
Operating temperature	T _a	-40	+85	°C	
Storage temperature	T _{stg}	-55	+125	°C	

*1 : The parameter is based on V_{SS} = AV_{SS1} = AV_{SS2} = 0 V.

*2 : Do not make a potential difference between AV_{SS} (AV_{SS1}/AV_{SS2}) pins and V_{SS} pin.

WARNING: Semiconductor devices can be permanently damaged by application of stress (voltage, current, temperature, etc.) in excess of absolute maximum ratings. Do not exceed these ratings.

■ RECOMMENDED OPERATING CONDITIONS

($V_{SS} = AV_{SS1} = AV_{SS2} = 0\text{ V}$)

Parameter	Symbol	Value		Unit	Remarks (circuit type)
		Min	Max		
Power supply voltage	V_{CC}	4.5	5.5	V	
	AV_{CC1}	4.5	5.5	V	*1, *2
	AV_{CC2}	4.5	5.5	V	*1, *3
“H” level input voltage	V_{IH1}	$0.7 \times V_{CC}$	$V_{CC} + 0.3$	V	(H)
	V_{IH1S}	$0.8 \times V_{CC}$	$V_{CC} + 0.3$	V	(D, E)
	V_{IH2S}	$0.6 \times V_{CC}$	$V_{CC} + 0.3$	V	(C)
“L” level input voltage	V_{IL1}	$V_{SS} - 0.3$	$0.3 \times V_{CC}$	V	(H)
	V_{IL1S}	$V_{SS} - 0.3$	$0.2 \times V_{CC}$	V	(D, E)
	V_{IL2S}	$V_{SS} - 0.3$	0.6	V	(C)
Analog input voltage	AV_{IN1}	0	AV_{CC1}	V	VIN pin
	AV_{IN2}	0	AV_{CC2}	V	YIN pin, CIN pin
Operating temperature	T_a	-40	+85	°C	

*1 : Do not make a potential difference between AV_{SS} (AV_{SS1}/AV_{SS2}) pins and V_{SS} pin.

*2 : It is possible to set $AV_{CC1} = AV_{SS}$ (AV_{SS1}/AV_{SS2}) when not using composite video signal (VIN pin, VOUT pin) .

*3 : It is possible to set $AV_{CC2} = AV_{SS}$ (AV_{SS1}/AV_{SS2}) when not using Y/C separated video signals (YIN pin, YOUT pin, CIN pin and COUT pin) .

WARNING: The recommended operating conditions are required in order to ensure the normal operation of the semiconductor device. All of the device's electrical characteristics are warranted when the device is operated within these ranges.

Always use semiconductor devices within their recommended operating condition ranges. Operation outside these ranges may adversely affect reliability and could result in device failure.

No warranty is made with respect to uses, operating conditions, or combinations not represented on the data sheet. Users considering application outside the listed conditions are advised to contact their representatives beforehand.

MB90050

■ ELECTRICAL CHARACTERISTICS

1. DC Characteristics

($V_{SS} = AV_{SS1} = AV_{SS2} = 0\text{ V}$, $T_a = -40\text{ °C}$ to $+85\text{ °C}$)

Parameter	Symbol	Pin name	Conditions	Value			Unit
				Min	Typ	Max	
"H" level output voltage	V_{OH}	All output pins	$V_{CC} = 4.5\text{ V}$, $I_{OH} = -4.0\text{ mA}$	4.0	—	—	V
"L" level output voltage	V_{OL}	All output pins	$V_{CC} = 4.5\text{ V}$, $I_{OL} = 4.0\text{ mA}$	—	—	0.4	V
Pull-up resistor	R_P	E, F	$V_{CC} = 5.5\text{ V}$	25	50	200	k Ω
Power supply current	I_{CC}	V_{CC}	$V_{CC} = 5.5\text{ V}$, 4FSC = 20 MHz, $f_{DC} = 20\text{ MHz}$	—	35	45	mA
Analog power supply current	I_A	AV_{CC1} , AV_{CC2}	$V_{CC} = AV_{CC1} = AV_{CC2} = 5.5\text{ V}$, 4FSC = 0 MHz, $AV_{IN1} = AV_{IN2} = 1.65\text{ V}$, No load	—	22	40	mA
ON resistor	R_{ON}	VIN-VOUT, YIN-YOUT, CIN-COUT	$V_{CC} = AV_{CC1} = AV_{CC2} = 4.5\text{ V}$, $I_{OL} = 100\text{ }\mu\text{A}$	—	215	310	Ω
OFF leak current	I_{OFF}	VIN, YIN, CIN	$V_{CC} = AV_{CC1} = AV_{CC2} = 5.5\text{ V}$, $AV_{IN1} = AV_{IN2} = 5.5\text{ V}$	—	0.1	10	μA
Output resistor	R_{OUT}	VOUT, YOUT, COUT	$V_{CC} = AV_{CC1} = AV_{CC2} = 4.5\text{ V}$, $I_{OL} = 100\text{ }\mu\text{A}$	100	—	1800	Ω

Analog Ladder Voltage

($V_{CC} = AV_{CC1} = AV_{CC2} = 5.0\text{ V}$)

Symbol	Parameter	Value			Unit
		Min	Typ	Max	
VOHR0	Resistance ladder voltage 00 (-40 IRE)	930	1000	1040	mV
VOHR1	Resistance ladder voltage 01 (-36 IRE)	988	1057	1098	mV
VOHR2	Resistance ladder voltage 02 (-32 IRE)	1046	1114	1156	mV
VOHR3	Resistance ladder voltage 03 (-28 IRE)	1104	1171	1214	mV
VOHR4	Resistance ladder voltage 04 (-24 IRE)	1162	1229	1272	mV
VOHR5	Resistance ladder voltage 05 (-20 IRE)	1220	1286	1330	mV
VOHR6	Resistance ladder voltage 06 (-16 IRE)	1278	1343	1388	mV
VOHR7	Resistance ladder voltage 07 (-12 IRE)	1336	1400	1446	mV
VOHR8	Resistance ladder voltage 08 (-8 IRE)	1394	1457	1504	mV
VOHR9	Resistance ladder voltage 09 (-4 IRE)	1452	1514	1562	mV
VOHR10	Resistance ladder voltage 10 (0 IRE)	1510	1571	1620	mV
VOHR11	Resistance ladder voltage 11 (4 IRE)	1568	1629	1678	mV
VOHR12	Resistance ladder voltage 12 (8 IRE)	1626	1686	1736	mV
VOHR13	Resistance ladder voltage 13 (12 IRE)	1684	1743	1794	mV
VOHR14	Resistance ladder voltage 14 (16 IRE)	1742	1800	1852	mV
VOHR15	Resistance ladder voltage 15 (20 IRE)	1800	1857	1910	mV
VOHR16	Resistance ladder voltage 16 (24 IRE)	1858	1914	1968	mV
VOHR17	Resistance ladder voltage 17 (28 IRE)	1916	1971	2026	mV
VOHR18	Resistance ladder voltage 18 (32 IRE)	1974	2029	2084	mV
VOHR19	Resistance ladder voltage 19 (36 IRE)	2032	2086	2142	mV
VOHR20	Resistance ladder voltage 20 (40 IRE)	2090	2143	2200	mV
VOHR21	Resistance ladder voltage 21 (44 IRE)	2148	2200	2258	mV
VOHR22	Resistance ladder voltage 22 (48 IRE)	2206	2257	2316	mV
VOHR23	Resistance ladder voltage 23 (52 IRE)	2264	2314	2374	mV
VOHR24	Resistance ladder voltage 24 (56 IRE)	2322	2371	2432	mV
VOHR25	Resistance ladder voltage 25 (60 IRE)	2380	2429	2490	mV
VOHR26	Resistance ladder voltage 26 (64 IRE)	2438	2486	2548	mV
VOHR27	Resistance ladder voltage 27 (68 IRE)	2496	2543	2606	mV
VOHR28	Resistance ladder voltage 28 (72 IRE)	2554	2600	2664	mV
VOHR29	Resistance ladder voltage 29 (76 IRE)	2612	2657	2722	mV
VOHR30	Resistance ladder voltage 30 (80 IRE)	2670	2714	2780	mV
VOHR31	Resistance ladder voltage 31 (84 IRE)	2728	2771	2838	mV
VOHR32	Resistance ladder voltage 32 (88 IRE)	2786	2829	2896	mV
VOHR33	Resistance ladder voltage 33 (92 IRE)	2844	2886	2954	mV
VOHR34	Resistance ladder voltage 34 (96 IRE)	2902	2943	3012	mV
VOHR35	Resistance ladder voltage 35 (100 IRE)	2960	3000	3070	mV

MB90050

MB90050 Palette Initial Value

- Pedestal level

Color code	Comment	Relative value	Absolute value	Register setting value
		PED (IRE)	PED (IRE)	PED (HEX)
—	Pedestal	0	40	0A

- Sink chip level

Color code	Comment	Relative value	Absolute value	Register setting value
		SYN (IRE)	SYN (IRE)	SYN (HEX)
—	Sink chip	-40	0	00

- Translucence level

Color code	Comment	Relative value	Absolute value	Register setting value
		HAN (IRE)	HAN (IRE)	HAN (HEX)
—	translucence	32	72	12

- Color burst level

Color code	Comment	Relative value				Absolute value				Register setting value			
		BST0 (IRE)	BST1 (IRE)	BST2 (IRE)	BST3 (IRE)	BST0 (IRE)	BST1 (IRE)	BST2 (IRE)	BST3 (IRE)	BST0 (HEX)	BST1 (HEX)	BST2 (HEX)	BST3 (HEX)
—	Burst	0	-24	0	24	40	16	40	64	0A	04	0A	10

- Y (COLOR)

Color code	Comment	Relative value	Absolute value	Register setting value
		Luminance (IRE)	YD (IRE)	YD (HEX)
15	White-1	100	140	23
14	Yellow-1	72	112	1C
13	Cyan-1	64	104	1A
12	Green-1	56	96	18
11	Magenta-1	40	80	14
10	Red-1	32	72	12
9	Blue-1	24	64	10
8	Black-1	16	56	0E
7	White-0	92	132	21
6	Yellow-0	64	104	1A
5	Cyan-0	56	96	18
4	Green-0	48	88	16
3	Magenta-0	32	72	12
2	Red-0	24	64	10
1	Blue-0	16	56	0E
0	Black-0	8	48	0C

• C (COLOR)

Color code	Comment	Relative value		Absolute value				Register setting value			
		Phase (degrees)	Amplitude (IRE)	0	90	180	270	CD0 (HEX)	CD1 (HEX)	CD2 (HEX)	CD3 (HEX)
15	White-1	0	0	40	40	40	40	0A	0A	0A	0A
14	Yellow-1	195	20	35	21	45	59	09	05	0B	0F
13	Cyan-1	284	36	5	49	75	31	01	0C	13	08
12	Green-1	241	30	14	25	66	55	03	06	11	0E
11	Magenta-1	61	30	66	55	14	25	11	0E	03	06
10	Red-1	104	36	75	31	5	49	13	08	01	0C
9	Blue-1	15	20	45	59	35	21	0B	0F	09	05
8	Black-1	0	0	40	40	40	40	0A	0A	0A	0A
7	White-0	0	0	40	40	40	40	0A	0A	0A	0A
6	Yellow-0	195	20	35	21	45	59	09	05	0B	0F
5	Cyan-0	284	36	5	49	75	31	01	0C	13	08
4	Green-0	241	30	14	25	66	55	03	06	11	0E
3	Magenta-0	61	30	66	55	14	25	11	0E	03	06
2	Red-0	104	36	75	31	5	49	13	08	01	0C
1	Blue-0	15	20	45	59	35	21	0B	0F	09	05
0	Black-0	0	0	40	40	40	40	0A	0A	0A	0A

• V (COLOR)

Color code	Comment	Absolute value				Register setting value			
		0	90	180	270	VD0 (HEX)	VD1 (HEX)	VD2 (HEX)	VD3 (HEX)
15	White-1	140	140	140	140	23	23	23	23
14	Yellow-1	107	93	117	131	1B	17	1D	21
13	Cyan-1	69	113	139	95	11	1C	23	18
12	Green-1	70	81	122	111	11	14	1F	1C
11	Magenta-1	106	95	54	65	1B	18	0D	10
10	Red-1	107	63	37	81	1B	10	09	14
9	Blue-1	69	83	59	45	11	15	0F	0B
8	Black-1	56	56	56	56	0E	0E	0E	0E
7	White-0	132	132	132	132	21	21	21	21
6	Yellow-0	99	85	109	123	19	15	1B	1F
5	Cyan-0	61	105	131	87	0F	1A	21	16
4	Green-0	62	73	114	103	0F	12	1D	1A
3	Magenta-0	98	87	46	57	19	16	0B	0E
2	Red-0	99	55	29	73	19	0E	07	12
1	Blue-0	61	75	51	37	0F	13	0D	09
0	Black-0	48	48	48	48	0C	0C	0C	0C

MB90050

• M (MONO)

Color code	Comment	Relative value	Absolute value	Register setting value
		Luminance (IRE)	MD (IRE)	MD (HEX)
15	Level-17	100	140	23
14	Level-16	80	120	1E
13	Level-15	68	108	1B
12	Level-14	60	100	19
11	Level-13	44	84	15
10	Level-12	36	76	13
9	Level-11	24	64	10
8	Level-10	16	56	0E
7	Level-07	92	132	21
6	Level-06	72	112	1C
5	Level-05	60	100	19
4	Level-04	52	92	17
3	Level-03	36	76	13
2	Level-02	28	68	11
1	Level-01	16	56	0E
0	Level-00	8	48	0C

Note : Minimum value for absolute value of IRE is 0.


Maximum value for absolute value of IRE is 140.

Relative value is the value when the pedestal level is 0IRE.


• D (DIGITAL)

Color code	Comment	Display color signal output pin						Register setting value
		DCOL5	DCOL4	DCOL3	DCOL2	DCOL1	DCOL0	DD (HEX)
15	Level-15	0	0	1	1	1	1	0F
14	Level-14	0	0	1	1	1	0	0E
13	Level-13	0	0	1	1	0	1	0D
12	Level-12	0	0	1	1	0	0	0C
11	Level-11	0	0	1	0	1	1	0B
10	Level-10	0	0	1	0	1	0	0A
9	Level-09	0	0	1	0	0	1	09
8	Level-08	0	0	1	0	0	0	08
7	Level-07	0	0	0	1	1	1	07
6	Level-06	0	0	0	1	1	0	06
5	Level-05	0	0	0	1	0	1	05
4	Level-04	0	0	0	1	0	0	04
3	Level-03	0	0	0	0	1	1	03
2	Level-02	0	0	0	0	1	0	02
1	Level-01	0	0	0	0	0	1	01
0	Level-00	0	0	0	0	0	0	00


• VOUT Output



• YOUT Output



• COUT Output



Note : Voltage of each output depends on palette setting value.

MB90050


2. AC Characteristics

(Ta = -40 °C to +85 °C, V_{CC} = 5.0 V±10 %, V_{SS} = 0 V)


Parameter	Symbol	Pin name	Value		Unit	Remarks
			Min	Max		
Shift clock cycle time	t _{CYC}	SCLK	250	—	ns	Refer to “Serial Input Timing”
Shift clock pulse width	t _{WCH}	SCLK	100	—	ns	
	t _{WCL}		100	—	ns	
Shift clock signal rise/fall time	t _{CR}	SCLK	—	200	ns	
	t _{CF}		—	200	ns	
Shift clock start time	t _{SS}	SCLK	100	—	ns	
Data setup time	t _{SU}	SIN	100	—	ns	
Data hold time	t _H	SIN	50	—	ns	
Chip select end time	t _{EC}	$\overline{\text{CS}}$	100	—	ns	
Chip select signal rise/fall time	t _{CR_C}	$\overline{\text{CS}}$	—	200	ns	
	t _{CF_C}		—	200	ns	
Horizontal sync signal rise time	t _{HR}	$\overline{\text{HSYNCI}}$	—	200	ns	Refer to “Vertical• Horizontal Sync Signal Input Timing”
Horizontal sync signal fall time	t _{HF}	$\overline{\text{HSYNCI}}$	—	200	ns	
Vertical sync signal rise time	t _{VR}	$\overline{\text{VSYNCI}}$	—	200	ns	
Vertical sync signal fall time	t _{VF}	$\overline{\text{VSYNCI}}$	—	200	ns	
Horizontal sync signal pulse width	t _{WH}	$\overline{\text{HSYNCI}}$	4.0	8.0	μs	
Vertical sync signal pulse width	t _{WV}	$\overline{\text{VSYNCI}}$	1	5	H*	
Field signal pulse width	t _{WFH}	FLDI	1	—	H*	Refer to “Field Signal Input Timing”
	t _{WFL}		1	—	H*	
Reset input pulse width	t _{WR}	$\overline{\text{RESET}}$	10	—	μs	Refer to “Reset Signal Input Timing”

* : 1 H is assumed to be one horizontal sync signal period.


• Serial Input Timing




• Vertical•Horizontal Sync Signal Input Timing



- Field Signal Input Timing



- Reset Signal Input Timing



3. Recommended Input Timings

H/V-separated sync signal input timing

Parameter	NTSC	PAL	Unit	Remarks
Vertical sync signal frequency	60 (59.94)	30	Hz	*1
Vertical sync signal pulse width	1 to 5	1 to 4	H	*2
Horizontal sync signal period	63.492 (63.5555)	64	μs	*1
Horizontal sync signal pulse width	4.19 to 5.71 (4.7 ± 0.1)	4.5 to 4.9	μs	*1

*1 : Parenthesized values are specifications for color information display.

*2 : 1 H is assumed to be one horizontal sync signal period.

4. Clock Timing

Parameter	Symbol	Pin	Value			Unit	Remarks
			Min	Typ	Max		
Dot clock for display*	f _{bc}	EXD XD	8	—	20	MHz	
Clock for color burst (NTSC) *	4FSC	EXS XS	—	14.318185	—	MHz	
Clock for color burst (PAL) *			—	17.734475	—	MHz	

* : Input the signal with a duty cycle of 50%.

5. Output Timings

(1) Horizontal timing

Symbol	NTSC (or simple PAL)	PAL (or simple NTSC)	Remarks
HPS	0	0	Refer to "NTSC/PAL Horizontal Timing".
EQP1E	34	42	
HPE	68	84	
BSTS	76	100	
BSTE	112	140	
HBLKE	143	186	
SEP1S	388	484	
EQP2S	455	568	
EQP2E	489	610	
SEP2S	842	1050	
HBLKS	888	1106	
IHCLR	910	1135 (1137) *	

* : Parenthesized values assume the last raster in each V cycle (field) .


Note : The values in the above list are 4FSC count values.

(2) Vertical timing

Symbol	NTSC (or simple NTSC)		PAL (or simple PAL)		Remarks
	Interlaced	Non interlaced	Interlaced	Non interlaced	
VPS	0	0	0	0	Refer to "NTSC Vertical Timing" and "PAL Vertical Timing".
VPE	6	6	5	5	
EQPE	12	12	10	10	
VBLKE	36	36	45	45	
VBLKS	519	519	620	620	
VPS	525	526	625	624	

Note : The values in the about list are 1/2 H count values. (1 H is assumed to be one horizontal sync signal period.)

• NTSC/PAL Horizontal Timing



• NTSC Vertical Timing

Even-numbered field


Composite video signal

Horizontal scanning line No.

Vertical sync interval

Vertical retrace blanking interval

Equalizing pulse interval



Odd-numbered field


Composite video signal

Horizontal scanning line No.

Vertical sync interval

Vertical retrace blanking interval


Equalizing pulse interval



• PAL Vertical Timing


First field

Color burst phase
 Composite video signal
 Horizontal scanning line No.
 Vertical sync interval
 Vertical retrace blanking interval
 Equalizing pulse interval




Second field

Color burst phase
 Composite video signal
 Horizontal scanning line No.
 Vertical sync interval
 Vertical retrace blanking interval
 Equalizing pulse interval




Third field

Color burst phase
 Composite video signal
 Horizontal scanning line No.
 Vertical sync interval
 Vertical retrace blanking interval
 Equalizing pulse interval



Fourth field

Color burst phase
 Composite video signal
 Horizontal scanning line No.
 Vertical sync interval
 Vertical retrace blanking interval
 Equalizing pulse interval



Notes : •◆ indicates the HSYNC positions in the equalizing pulse intends.
 • The arrows marks indicate the phase of color subcarrier. (↑ : +135°, ↓ : -135°)

MB90050

■ COMMAND LIST

Command no.	Command code/data													Function
	15 to 12	11	10	9	8	7	6	5	4	3	2	1	0	
0	0000	AY3	AY2	AY1	AY0	FL	0	AX5	AX4	AX3	AX2	AX1	AX0	VRAM write address setting
1	0001	MS1	MS0	MM1	MM0	MB3	MB2	MB1	MB0	MC3	MC2	MC1	MC0	Character data setting 1
2	0010	MR	MG	MBL	M8	M7	M6	M5	M4	M3	M2	M1	M0	Character data setting 2
3	0011	LHS	LW2	LW1	LW0	LFD	LFC	LFB	LFA	LF3	LF2	LF1	LF0	Line control data setting 1
4	0100	LDS	0	LG1	LG0	LD	LE	LM1	LM0	L3	L2	L1	L0	Line control data setting 2
5-0	0101	0	0	0	0	SDS	UDS	0	DSP	0	0	0	0	Screen output control 1
5-1	0101	0	1	FM1	FM0	BT1	BT0	BD1	BD0	0	0	0	0	Screen output control 1
5-2	0101	1	0	0	Y8	Y7	Y6	Y5	Y4	Y3	Y2	Y1	Y0	Vertical display position control
5-3	0101	1	1	0	X8	X7	X6	X5	X4	X3	X2	X1	X0	Horizontal display position control
6-0	0110	0	0	0	0	0	HB2	HB1	HB0	0	HA2	HA1	HA	Character vertical size control
6-1	0110	0	1	0	0	BH3	BH2	BH1	BH0	BS3	BS2	BS1	BS0	Shaded background frame color control
6-2	0110	1	0	TC	HC	TC3	TC2	TC1	TC0	HC3	HC2	HC1	HC0	Transparent/semi-transparent colors control
6-3	0110	1	1	GF	GC	GF3	GF2	GF1	GF0	GC3	GC2	GC1	GC0	Graphic color control
7-3	0111	1	1	1	0	0	0	0	0	U3	U2	U1	U0	Screen background control
8-1	1000	0	1	SD1	SD0	SM7	SM6	SM5	SM4	SM3	SM2	SM1	SM0	Sprite character control 1
8-2	1000	1	0	1	SBL	0	SH2	SH1	SH0	0	0	0	0	Sprite character control 2
9-0	1001	0	0	SY9	SY8	SY7	SY6	SY5	SY4	SY3	SY2	SY1	SY0	Sprite character control 3
9-1	1001	1	0	SX9	SX8	SX7	SX6	SX5	SX4	SX3	SX2	SX1	SX0	Sprite character control 4

(Continued)


(Continued)

Command no.	Command code/data													Function
	15 to 12	11	10	9	8	7	6	5	4	3	2	1	0	
11-0	1011	0	0	FDS	FDC	MC	NP2	NP1	NP0	IN1	IN0	IE1	IE0	Sync control 1
11-1	1011	0	1	0	0	VIX	HIX	0	0	VHE	HE	0	0	Sync control 2
11-3	1011	1	1	0	0	0	H2	H1	H0	0	F2	F1	F0	Sync detection control
12-0	1100	0	0	STO	BUO	VSO	HSO	CSO	VBO	FDO	DHO	DBO	DCO	Output pin control 1
12-1	1100	0	1	STX	BUX	VOX	HOX	COX	VBX	FDX	DHX	DBX	DCX	Output pin control 2
12-2	1100	1	0	STU	BUU	VSU	HSU	CSU	VBU	FDU	0	0	0	Output pin control 3
12-3	1100	1	1	CKO	FSO	CKS	FSS	0	0	PO3	PO2	PO1	PO0	Output pin control 4
13-0	1101	0	0	0	PLV	PLY	PLC	PLM	PLD	PL3	PL2	PL1	PL0	Color palette setting
13-1	1101	1	AA2	AA1	AA0	0	0	AD5	AD4	AD3	AD2	AD1	AD0	Analog level control
14-0	1110	0	0	0	0	0	0	0	FRS	0	0	FA1	FA0	Font RAM setting 1
14-1	1110	0	1	0	0	0	0	0	0	0	FR2	FR1	FR0	Font RAM setting 2












































Note : When a reset signal is input (L level signal input to $\overline{\text{RESET}}$ pin), the screen output control 1 (command 5 to command 0) bits (SDS, UDS and DSP) and the output pin control 1 to 4 (command 12-0 to command 12-3) bits are initialized to "0". The color palette setting (command 13-0) and analog level control (command 13-1) bits are internally set to their predetermined initial values. The contents of other register bits, VRAM and font RAM are undefined. After reset input (release) is completed, set all command and font RAM settings.

MB90050


■ SAMPLE CIRCUIT

















































■ MB90050-001 FONT DATA (MB90050-001 is typical product.)

							
000	001	002	003	004	005	006	007
							
008	009	00A	00B	00C	00D	00E	00F
							
010	011	012	013	014	015	016	017
							
018	019	01A	01B	01C	01D	01E	01F
							
020	021	022	023	024	025	026	027
							
028	029	02A	02B	02C	02D	02E	02F
							
030	031	032	033	034	035	036	037
							
038	039	03A	03B	03C	03D	03E	03F































































(Continued)

































































(Continued)

							
080	081	082	083	084	085	086	087
							
088	089	08A	08B	08C	08D	08E	08F
							
090	091	092	093	094	095	096	097
							
098	099	09A	09B	09C	09D	09E	09F
							
0A0	0A1	0A2	0A3	0A4	0A5	0A6	0A7
							
0A8	0A9	0AA	0AB	0AC	0AD	0AE	0AF
							
0B0	0B1	0B2	0B3	0B4	0B5	0B6	0B7
							
0B8	0B9	0BA	0BB	0BC	0BD	0BE	0BF



























































(Continued)

							
0C0	0C1	0C2	0C3	0C4	0C5	0C6	0C7
							
0C8	0C9	0CA	0CB	0CC	0CD	0CE	0CF
							
0D0	0D1	0D2	0D3	0D4	0D5	0D6	0D7
							
0D8	0D9	0DA	0DB	0DC	0DD	0DE	0DF
							
0E0	0E1	0E2	0E3	0E4	0E5	0E6	0E7
							
0E8	0E9	0EA	0EB	0EC	0ED	0EE	0EF
							
0F0	0F1	0F2	0F3	0F4	0F5	0F6	0F7
							
0F8	0F9	0FA	0FB	0FC	0FD	0FE	0FF

(Continued)

							
100	101	102	103	104	105	106	107
							
108	109	10A	10B	10C	10D	10E	10F
							
110	111	112	113	114	115	116	117
							
118	119	11A	11B	11C	11D	11E	11F
							
120	121	122	123	124	125	126	127
							
128	129	12A	12B	12C	12D	12E	12F
							
130	131	132	133	134	135	136	137
							
138	139	13A	13B	13C	13D	13E	13F

(Continued)





















































 140	 141	 142	 143	 144	 145	 146	 147
 148	 149	 14A	 14B	 14C	 14D	 14E	 14F
 150	 151	 152	 153	 154	 155	 156	 157
 158	 159	 15A	 15B	 15C	 15D	 15E	 15F
 160	 161	 162	 163	 164	 165	 166	 167
 168	 169	 16A	 16B	 16C	 16D	 16E	 16F
 170	 171	 172	 173	 174	 175	 176	 177
 178	 179	 17A	 17B	 17C	 17D	 17E	 17F

(Continued)

ü	é	â	ä	à	ä	ç	ê
180	181	182	183	184	185	186	187
ë	è	ï	î	ì	Ä	Å	É
188	189	18A	18B	18C	18D	18E	18F
æ	Æ	ô	ö	ò	û	ù	ÿ
190	191	192	193	194	195	196	197
ö	Ü	Ç	£	¥	℞	ƒ	á
198	199	19A	19B	19C	19D	19E	19F
í	ó	ú	ñ	Ñ	º	º	¿
1A0	1A1	1A2	1A3	1A4	1A5	1A6	1A7
Γ	Γ	½	¼	ı	«	»	α
1A8	1A9	1AA	1AB	1AC	1AD	1AE	1AF
β	Γ	π	Σ	σ	μ	γ	Ω
1B0	1B1	1B2	1B3	1B4	1B5	1B6	1B7
Θ	Ω	δ	ω	ρ	€	η	≡
1B8	1B9	1BA	1BB	1BC	1BD	1BE	1BF

(Continued)

(Continued)

							
1C0	1C1	1C2	1C3	1C4	1C5	1C6	1C7
							
1C8	1C9	1CA	1CB	1CC	1CD	1CE	1CF
							
1D0	1D1	1D2	1D3	1D4	1D5	1D6	1D7
							
1D8	1D9	1DA	1DB	1DC	1DD	1DE	1DF
							
1E0	1E1	1E2	1E3	1E4	1E5	1E6	1E7
							
1E8	1E9	1EA	1EB	1EC	1ED	1EE	1EF
							
1F0	1F1	1F2	1F3	1F4	1F5	1F6	1F7
							
1F8	1F9	1FA	1FB	1FC	1FD	1FE	1FF

■ ORDERING INFORMATION


Part number	Package	Remarks
MB90050PF	48-pin, plastic QFP (FPT-48P-M15)	

MB90050

■ PACKAGE DIMENSION

48-pin, plastic QFP
(FPT-48P-M15)

Note 1) * : These dimensions do not include resin protrusion.
 Note 2) Pins width and pins thickness include plating thickness.
 Note 3) Pins width do not include tie bar cutting remainder.



© 2003 FUJITSU LIMITED F48025S-c-3-4

Dimensions in mm (inches)

Note : The values in parentheses are reference values.

MEMO

MEMO

MEMO

FUJITSU MICROELECTRONICS LIMITED

Shinjuku Dai-Ichi Seimei Bldg. 7-1, Nishishinjuku 2-chome, Shinjuku-ku,
Tokyo 163-0722, Japan Tel: +81-3-5322-3347 Fax: +81-3-5322-3387
<http://jp.fujitsu.com/fml/en/>

For further information please contact:

North and South America

FUJITSU MICROELECTRONICS AMERICA, INC.
1250 E. Arques Avenue, M/S 333
Sunnyvale, CA 94085-5401, U.S.A.
Tel: +1-408-737-5600 Fax: +1-408-737-5999
<http://www.fma.fujitsu.com/>

Europe

FUJITSU MICROELECTRONICS EUROPE GmbH
Pittlerstrasse 47, 63225 Langen,
Germany
Tel: +49-6103-690-0 Fax: +49-6103-690-122
<http://emea.fujitsu.com/microelectronics/>

Korea

FUJITSU MICROELECTRONICS KOREA LTD.
206 KOSMO TOWER, 1002 Daechi-Dong,
Kangnam-Gu, Seoul 135-280
Korea
Tel: +82-2-3484-7100 Fax: +82-2-3484-7111
<http://www.fmk.fujitsu.com/>

Asia Pacific

FUJITSU MICROELECTRONICS ASIA PTE LTD.
151 Lorong Chuan, #05-08 New Tech Park,
Singapore 556741
Tel: +65-6281-0770 Fax: +65-6281-0220
<http://www.fujitsu.com/sg/services/micro/semiconductor/>

FUJITSU MICROELECTRONICS SHANGHAI CO., LTD.
Rm.3102, Bund Center, No.222 Yan An Road(E),
Shanghai 200002, China
Tel: +86-21-6335-1560 Fax: +86-21-6335-1605
<http://cn.fujitsu.com/fmc/>

FUJITSU MICROELECTRONICS PACIFIC ASIA LTD.
10/F., World Commerce Centre, 11 Canton Road
Tsimshatsui, Kowloon
Hong Kong
Tel: +852-2377-0226 Fax: +852-2376-3269
<http://cn.fujitsu.com/fmc/tw>

All Rights Reserved.

The contents of this document are subject to change without notice.

Customers are advised to consult with sales representatives before ordering.

The information, such as descriptions of function and application circuit examples, in this document are presented solely for the purpose of reference to show examples of operations and uses of FUJITSU MICROELECTRONICS device; FUJITSU MICROELECTRONICS does not warrant proper operation of the device with respect to use based on such information. When you develop equipment incorporating the device based on such information, you must assume any responsibility arising out of such use of the information.

FUJITSU MICROELECTRONICS assumes no liability for any damages whatsoever arising out of the use of the information.

Any information in this document, including descriptions of function and schematic diagrams, shall not be construed as license of the use or exercise of any intellectual property right, such as patent right or copyright, or any other right of FUJITSU MICROELECTRONICS or any third party or does FUJITSU MICROELECTRONICS warrant non-infringement of any third-party's intellectual property right or other right by using such information. FUJITSU MICROELECTRONICS assumes no liability for any infringement of the intellectual property rights or other rights of third parties which would result from the use of information contained herein.

The products described in this document are designed, developed and manufactured as contemplated for general use, including without limitation, ordinary industrial use, general office use, personal use, and household use, but are not designed, developed and manufactured as contemplated (1) for use accompanying fatal risks or dangers that, unless extremely high safety is secured, could have a serious effect to the public, and could lead directly to death, personal injury, severe physical damage or other loss (i.e., nuclear reaction control in nuclear facility, aircraft flight control, air traffic control, mass transport control, medical life support system, missile launch control in weapon system), or (2) for use requiring extremely high reliability (i.e., submersible repeater and artificial satellite).

Please note that FUJITSU MICROELECTRONICS will not be liable against you and/or any third party for any claims or damages arising in connection with above-mentioned uses of the products.

Any semiconductor devices have an inherent chance of failure. You must protect against injury, damage or loss from such failures by incorporating safety design measures into your facility and equipment such as redundancy, fire protection, and prevention of over-current levels and other abnormal operating conditions.

Exportation/release of any products described in this document may require necessary procedures in accordance with the regulations of the Foreign Exchange and Foreign Trade Control Law of Japan and/or US export control laws.

The company names and brand names herein are the trademarks or registered trademarks of their respective owners.