

RED PROBE+

Red Probe+ is a High Speed USB debug probe specially designed for use with ARM-based Microcontrollers.

Featuring complete integration with Red Suite, Red Probe allows high speed download to RAM and direct programming of on-chip Flash.

When used with Cortex-M3 targets, built-in support for SWV allows full support for data trace, instruction and exception profiling and application sourced diagnostics.

Together with Red Suite, Red Probe provides a complete development and debug environment for ARM-based micro-controllers.

Priced at \$150



Red Probe+™

JTAG/SWD Debug Probe

Now High Speed USB for same price as original Red Probe



Features

- USB 2.0 High Speed — up to 480Mbps.
- Faster all round debug including stepping.
- JTAG/SWD clock up to 30MHz!.
- Self powered from USB host.
- Wide target voltage range: 1.5V - 3.5V.
- Switchable protocol support:
 - ARM JTAG SWD, and SWV.
- Supports multiple standard JTAG connectors:
 - 20-pin 0.1" pitch (supplied),
 - 10-pin 0.05" pitch (1.27mm) pitch (option)
- Programmable SWV runtime trace capture.
- Hardware and Software Breakpoints.
- Integrated high-speed FLASH programming with Red Suite.
- One of the fastest download and FLASH programming algorithms in the industry:
 - Up to 5M Bytes/s download to RAM,
 - Up to 40K Bytes/s flash programming.
- Fully integrated with Red Suite.



Code Red Technologies Inc. : 648 Chenery Street, San Francisco, California 94131, USA
Code Red Technologies Ltd. : 6b Lower Court, Copley Hill Business Park, Cambridge Road, Babraham, Cambridge, CB22 3GN, UK
Tel: US Office: +1 415 349 4601; EU/UK Office +44 1223 515 768
Email: information@code-red-tech.com Web: www.code-red-tech.com

© 2011-2012 Code Red Technologies. All brand names or product names are the property of their respective holders. Neither the whole nor any part of the information contained in, or the product described in this document may be adapted or reproduced in any material form except with the prior written permission of the copyright holder. The product described in this document is subject to continuous improvement and development. This document is intended only to provide information to the reader about the product.