



**Genesys Logic, Inc.**

---

# **GL845**

**High Speed USB 2.0  
2-in-1 Scanner Controller  
with ADF**

**Product Overview**



## Copyright

Copyright © 2012 Genesys Logic, Inc. All rights reserved. No part of the materials shall be reproduced in any form or by any means without prior written consent of Genesys Logic, Inc.

## Ownership and Title

Genesys Logic, Inc. owns and retains of its right, title and interest in and to all materials provided herein. Genesys Logic, Inc. reserves all rights, including, but not limited to, all patent rights, trademarks, copyrights and any other propriety rights. No license is granted hereunder.

## Disclaimer

All Materials are provided “as is”. Genesys Logic, Inc. makes no warranties, express, implied or otherwise, regarding their accuracy, merchantability, fitness for any particular purpose, and non-infringement of intellectual property. In no event shall Genesys Logic, Inc. be liable for any damages, including, without limitation, any direct, indirect, consequential, or incidental damages. The materials may contain errors or omissions. Genesys Logic, Inc. may make changes to the materials or to the products described herein at anytime without notice.

## Genesys Logic, Inc.

12F., No. 205, Sec. 3, Beixin Rd., Xindian Dist. 231,

New Taipei City, Taiwan

Tel : (886-2) 8913-1888

Fax : (886-2) 6629-6168

<http://www.genesyslogic.com>



### GENERAL DESCRIPTION


Genesys Logic's single-chip GL845 (GeneScan™ series) is a high speed, high performance and rich scalability controller for scanner with fast ADF function. It successfully integrates scanner function ASIC and USB 2.0 interface controller into one single-chip. With its high performance design architecture, GL845 is not only ready for supporting CIS or CCD image sensors (600, 1200, 2400, 3200, 3600, 4800 and 9600dpi resolution) that are used in sheet fed, flatbed or transparency scanners, but is able to co-work with unipolar or bipolar stepping motors. Advanced features of GL845 include five motor acceleration/ deceleration curve tables for high speed motor moving.

## FEATURES

- Highly integrated scanner controller chip (2-in-1; Scanner Controller and USB 2.0 Interface)
- USB 2.0 High Speed (480Mbit) compliant
- Designed for sheetfed, flatbed and transparency scanners
- Embedded RISC CPU for USB protocol handling
- Support MCU with SPI interfaces for special application in 208 pin package
- Support single AFE for dual head scanning
- Support two chips application for fast dual head scanning
- Supports external 24Kbytes flash ROM or internal 24Kbyte mask ROM
- Firmware online-download for external flash ROM programming
- 12MHz low frequency clock input for better EMI
- Adjustable working clock of scanner controller for different usage (12M, 24M, 30M, 40M, 48M, 60MHz)
- Supports linear or stagger CCD, such as NEC, Toshiba or Sony CCD
- Available sensor types: 600, 1200, 2400, 3200, 3600, 4800 and 9600 dpi color CIS or CCD
- Multi-TG control for CCD (separately controls the R/G/B exposure time)
- Shutter-control for CCD (separately controls the R/G/B exposure time)
- Supports two scanning types: pixel-by-pixel (pixel rate), line-by-line (line rate)
- Support 48-bits color, 16-bits gray and 1-bit line-art
- “True gray” with R, G and B weightings
- 16 bits white/dark shading and 16 bits Gamma correction
- Supports RS232 interface for special applications
- Supports EEPROM (93C46) interface for special applications
- Supports ADF (Auto-Document-Feeder) function with document, ADF and cover sensors
- Supports auto-ADF with automatically feeding in, automatically scanning and automatically feeding out
- Lines packing for stagger CCD or R/G/B line differences
- Fine CDS sampling adjustment to avoid the digital noise influence (8.33ns adjustment)
- Digital average and hardware deletion for various resolutions
- Hardware deletion for various resolutions (from 9600~1dpi with 1dpi decrement)
- Supports 1M\*16, 4M\*16, 8M\*16, 16M\*16 and 32M\*16 SDRAM
- Supports up to 1 G bits size SDRAM (implements two SDRAM)
- Supports 5 acceleration/deceleration motor tables for high speed motor moving and wall hitting protection
- Supports controllable bipolar motor in full, half, quarter and eighth steps moving
- Supports controllable unipolar motor in full and half steps moving
- Supports V-reference automatic control for motor driver Ics
- Build-in PWM control phase for unipolar motors


## BLOCK DIAGRAM

### USB 2.0 System Block Diagram



USB 2.0 System Block Diagram

### Function Block Diagram



Function Block Diagram