

2A Avg.

200 Volts


SBD

20KHA20

■最大定格 Maximum Ratings

Item	Symbol	Conditions	Unit
くり返しピーク逆電圧 Repetitive Peak Reverse Voltage	V_{RRM}	200	V
平均整流電流 Average Rectified Forward Current	I_O	50Hz, 正弦半波通電抵抗負荷 50Hz Half Sine Wave Resistive Load	2.0 1.6
実効順電流 R.M.S. Forward Current	$I_F(RMS)$		3.14
サージ順電流 Surge Forward Current	I_{FSM}	40 50Hz正弦半波, 1サイクル, 非くり返し 50Hz Half Sine Wave, 1cycle, Non-repetitive	A
動作接合温度範囲 Operating Junction Temperature Range	T_{jw}		-40~+150
保存温度範囲 Storage Temperature Range	T_{stg}		-40~+150

■OUTLINE DRAWING(mm)



■電氣的・熱的特性 Electrical/Thermal Characteristics

Item	Symbol	Conditions	Min.	Typ.	Max.	Unit
ピーク逆電流 Peak Reverse Current	I_{RM}	$T_j=25^{\circ}C, V_{RM}=V_{RRM}$	—	—	200	μA
ピーク順電圧 Peak Forward Voltage	V_{FM}	$T_j=25^{\circ}C, I_{FM}=3A$	—	—	0.90	V
熱抵抗 Thermal Resistance	$R_{th(j-l)}$	接合部・リード間 Junction to Lead	—	—	17	$^{\circ}C/W$
	$R_{th(j-a)}$	接合部・周囲間 Junction to Ambient	—	—	70	$^{\circ}C/W$

* Print Lands =5×5mm, Both sides

■定格・特性曲線

