

60A Avg.

60 Volts


SBD

KSQ60A06E

■最大定格 Maximum Ratings

Item	Symbol	Conditions		Unit
くり返しピーク逆電圧 Repetitive Peak Reverse Voltage	$V_{RRM}$	60		V
平均整流電流 Average Rectified Forward Current	$I_O$	50Hz、正弦半波通電抵抗負荷 50Hz Half Sine Wave Resistive Load	$T_c=87^\circ\text{C}$	60 A
実効順電流 R.M.S. Forward Current	$I_{F(RMS)}$	94.2		A
サージ順電流 Surge Forward Current	$I_{FSM}$	700	50Hz正弦半波、1サイクル、非くり返し 50Hz Half Sine Wave, 1cycle, Non-repetitive	A
動作接合温度範囲 Operating Junction Temperature Range	$T_{jw}$	-40~+150		$^\circ\text{C}$
保存温度範囲 Storage Temperature Range	$T_{stg}$	-40~+150		$^\circ\text{C}$
締付トルク Mounting torque	$F_{tor}$	推奨値 Recommended Value		0.5 N·m

■OUTLINE DRAWING(mm)



■電氣的・熱的特性 Electrical/Thermal Characteristics

Item	Symbol	Conditions	Min.	Typ.	Max.	Unit
ピーク逆電流 Peak Reverse Current	$I_{RM}$	$T_j=25^\circ\text{C}, V_{RM}=V_{RRM}$	—	—	40	mA
ピーク順電圧 Peak Forward Voltage	$V_{FM}$	$T_j=25^\circ\text{C}, I_{FM}=60\text{A}$	—	—	0.71	V
熱抵抗 Thermal Resistance	$R_{th(j-c)}$	接合部・ケース間 Junction to Case	—	—	0.75	$^\circ\text{C}/\text{W}$

■定格・特性曲線

