

3A Avg.

600 Volts


FRED

30PUA60

■最大定格 Maximum Ratings

Item	Symbol	Conditions	Unit
くり返しピーク逆電圧 Repetitive Peak Reverse Voltage	V_{RRM}	600	V
平均整流電流 Average Rectified Forward Current	I_O	50Hz, 正弦半波通電抵抗負荷 50Hz Half Sine Wave Resistive Load	1.8 3.0
実効順電流 R.M.S. Forward Current	$I_F(RMS)$		4.71
サージ順電流 Surge Forward Current	I_{FSM}	55 50Hz正弦半波, 1サイクル, 非くり返し 50Hz Half Sine Wave, 1cycle, Non-repetitive	A
動作接合温度範囲 Operating Junction Temperature Range	T_{jw}		-40~+150
保存温度範囲 Storage Temperature Range	T_{stg}		-40~+150

■OUTLINE DRAWING(mm)



■電氣的・熱的特性 Electrical/Thermal Characteristics

Item	Symbol	Conditions	Min.	Typ.	Max.	Unit
ピーク逆電流 Peak Reverse Current	I_{RM}	$T_j=25^\circ C, V_{RM}=V_{RRM}$	—	—	20	μA
ピーク順電圧 Peak Forward Voltage	V_{FM}	$T_j=25^\circ C, I_{FM}=3A$	—	—	2.35	V
逆回復時間 Reverse Recovery Time	t_{rr}	$I_{FM}=3A, -di/dt=50 A/\mu s, T_j=25^\circ C$	—	—	32	ns
熱抵抗 Thermal Resistance	$R_{th(j-a)}$	接合部・周囲間 Junction to Ambient	—	—	34	$^\circ C/W$
	$R_{th(j-l)}$	接合部・リード間 Junction to Lead	—	—	8	$^\circ C/W$

*銅フィン付き(両側) / With Cu Fin (20*20*1, L=5mm, Both sides)

■定格・特性曲線

