




XMR XMU

HIGH VOLTAGE RECOVERY FOR X-RAY AND INDUSTRIAL APPLICATIONS STANDARD AND FAST RECOVERY TYPES

- EPOXY MOLDED PACKAGE
- PLATINUM DOPED
- AVALANCHE CAPABILITY

X-RAY BOARD ASSEMBLIES
ALSO AVAILABLE. INQUIRE.



ELECTRICAL CHARACTERISTICS (at TA=25°C Unless Otherwise Specified)

Type	XMR 5	XMR 10	XMR 15	XMU 5	XMU 10	
Peak Reverse Voltage, Operating, $V_{R(OPER)}$	5	10	15	5	9	kV
Peak Reverse Voltage, Test, $V_{R(TEST)}$	5.5	11	16.5	5.5	10	kV
Average Rectified Forward Current in 55 °C Oil (Fig. 1)	500	300				mA
Max. Peak Surge Current, I_{FRM} 1/2 Cycles @ 60Hz (Non Repetitive), Fig. 2	100					AMPS
Max. Peak Surge Current, I_{FRM} , 10 Cycles @ 60Hz	25					AMPS
Max. Forward Voltage Drop, $V_{FM}@$, I_F	$I_F=500$ mA	$I_F=300$ mA				V
	10	17	21	11	21	
Max. DC Reverse Current, I_{RM} , @ $V_{R(TEST)}$ and 25 °C,	5					μA
Max. DC Reverse Current, I_{RM} , @ $V_{R(TEST)}$ and 100 °C,	500	300				μA
Max. Reverse Recovery Time, T_{RR} $I_F=50$ mA, $I_R=100$ mA, $I_{RR}=25$ mA, (Fig. 4)	150	135		75		ns
Ambient Operating Temperature Range, T_A	-55 to +125°C					
Storage Temperature Range, T_{STG}	-55 to +150°C					

If operated over 10,000 v/inch in length, devices should be immersed in oil or re-encapsulated.

FIG.1

OUTPUT CURRENT vs AMBIENT TEMPERATURE




FIG.2

NON-REPETITIVE SURGE CURRENT

PEAK SURGE CURRENT VS
NUMBER OF CYCLES AT 60 Hz
(SINE WAVE INPUT) AND $T_A = 25^\circ\text{C}$




FIG.3

MECHANICAL

Max. lead temperature for soldering, $\frac{1}{8}$ " from body, 10 seconds @ 260°C






FIG.4

REVERSE RECOVERY TEST METHOD

RECOVERY WAVE FORM



RECOVERY TEST CIRCUIT



R_1, R_2 NON-INDUCTIVE RESISTORS
PULSE GENERATOR-HEWLETT PACKARD 214A OR EQUIV.
1 KC REP.RATE, 10μ SEC. PULSE WIDTH
ADJUST PULSE AMPLITUDE FOR PEAK I_R

ELECTRONIC DEVICES, INC. DESIGNERS AND MANUFACTURERS OF SOLID STATE DEVICES SINCE 1951.

21 GRAY OAKS AVENUE * YONKERS, NEW YORK 10710 914-965-4400 * FAX 914-965-5531 * 1-800-678-0828

e-mail:sales@edidiodes.com * website: <http://www.edidiodes.com>