



CEP300AXE, CEP300BXE, CEP300CXE and CEP300FXE **300W XENON POWER SUPPLY with PFC**



The CEP300AXE, CEP300BXE, CEP300CXE, and CEP300FXE power supplies are designed to run Xenon arc lamps in a constant-power mode. All CEP models have PFC.

The CEP300 power supply is designed to run Xenon arc lamps in a constant-power mode. The supply is designed to run the Osram XBO 300 and Cermamax® Xenon family lamps. The output power is adjustable from 270 to 315 Watts with a built-in potentiometer. EMI line-filtering is built-in to the unit. The supply includes an isolated +12V output for powering external fans or electronics.

The CEP300 power supply is designed to switch to constant-current mode by removing two easily accessible shorting jumpers.

Active Power Factor Correction (PFC) to meet EMC limits for harmonic current emissions, and limitations of voltage fluctuations and flicker.

CERMAX

Key Features

- Line Input: 100 - 240 VAC, $\pm 10\%$, 50 - 60 Hz, 6.5 Arms max.
- Environmental: 0°C to 40°C operating.
- Altitude: -1,000 ft. to 12,000 ft. (-305 m to 3658 m) MSL.
- Weight: 2.7 lbs. (1.2 Kg).
- Dimensions: 6.50" x 4.65" x 2.60" tall (165 mm x 114 mm x 66 mm tall).

Ignitor:

- 25 KV ignition spike. Positive-side ignition
- Minimum repetition rate is 10 strikes/second at 90VAC.
- Ignition pulses will continue for ± 1 seconds. This feature may be disabled via jumper, in which case the ignition pulses will continue until the lamp ignites.
- Ignitor Life: > 100,000 strikes.

CEP300AXE, CEP300BXE, CEP300CXE, and CEP300FXE 300W XENON POWER SUPPLY with PFC

Output power: 270 - 315 Watts, constant power

Output voltage compliance: 12.0 to 17.0 V
operating, > 110 VDC during ignition.

Output regulation: output power held to within
± 5% over all input, output, and environmental
conditions.

Output current: 17.0 to 22.0 Adc

Output ripple: < 5%*

Efficiency: > 70% at 300 W output, 120 VAC input

Thermal protection: Ballast is disabled when heat-
sink temperature exceeds 90°C. Unit will
automatically restart after cooling down.

Isolated Auxiliary output (SELV rated): +12.5VDC
± 2%, 2.0 A max.

**Optically Isolated Status and Control Connector
(SELV rated):**

- Remote enable
- Lamp lit status
- Linear-response remote intensity
control
- Lamp over-voltage/under-voltage
indicator

Ground leakage:

- CEP300AXE < 300 µA
- CEP300BXE < 10 µA
- CEP300CXE < 100 µA
- CEP300FXE < 50 µA

*ripple is measured in a DC to 20 MHz bandwidth

Regulatory Compliance

Approved to UL2601 (E177225).

Complies with EN55011 Class B Emissions.

Meets EN 61000-3-2 and EN61000-3-3.

CE-marked.



About Excelitas Technologies

Excelitas Technologies is a global technology leader
focused on delivering innovative, customized solutions to
meet the lighting, detection and other high-performance
technology needs of OEM customers.

From medical lighting to analytical instrumentation,
clinical diagnostics, industrial, safety and security and
aerospace and defense applications, Excelitas
Technologies is committed to enabling our customers'
success in their end-markets.

Excelitas Technologies has approximately 3,000
employees in North America, Europe and Asia, serving
customers across the world.

**Excelitas Technologies
Illumination, Inc.**
44370 Christy Street
Fremont, California
94538-3180 USA
Telephone: (+1) 510.979.6500
Toll-free: (+1) 800.775.6786
Fax: (+1) 510.687.1140
shortarcxenon.na@excelitas.com

Excelitas Technologies
47 Ayer Rajah Crescent #06-12
Singapore 139947
Telephone: (+65) 6775 2022 (Main Line)
Telephone: (+65) 6770 4366
(Customer Service Hotline)
Fax: (+65) 6778 1752
shortarcxenon.asia@excelitas.com

**Excelitas Technologies
GmbH & Co. KG**
Wenzel-Jaksch-Str. 31
D-65199 Wiesbaden
Germany
Telephone: (+49) 611 492 430
Fax: (+49) 611 492 165
shortarcxenon.europe@excelitas.com

Excelitas Technologies
East Tower 4th Floor,
Otemachi First Square
1-5-1 Otemachi, Chiyoda-ku,
Tokyo 100-0004
Telephone: (+81) 3-5219-1228
Fax: (+81) 3-5219-120
shortarcxenon.asia@excelitas.com

For a complete listing of our global offices, visit www.excelitas.com/locations

© 2012 Excelitas Technologies Corp. All rights reserved. The Excelitas logo and design are registered trademarks of Excelitas Technologies Corp. All other trademarks
not owned by Excelitas Technologies or its subsidiaries that are depicted herein are the property of their respective owners. Excelitas reserves the right to change this
document at any time without notice and disclaims liability for editorial, pictorial or typographical errors.

