

SEMiX252GB176HDs



SEMiX® 2s

Trench IGBT Modules


SEMiX252GB176HDs

Features

- Homogeneous Si
- Trench = Trenchgate technology
- $V_{CE(sat)}$ with positive temperature coefficient
- UL recognised file no. E63532

Typical Applications*

- AC inverter drives
- UPS
- Electronic welders



GB

Absolute Maximum Ratings				
Symbol	Conditions		Values	Unit
IGBT				
V _{CES}	T _j = 25 °C		1700	V
I _C	T _j = 150 °C	T _c = 25 °C	246	A
		T _c = 80 °C	175	A
I _{Cnom}			150	A
I _{CRM}	I _{CRM} = 2xI _{Cnom}		300	A
V _{GES}			-20 ... 20	V
t _{psc}	V _{CC} = 1000 V V _{GE} ≤ 20 V V _{CES} ≤ 1700 V	T _j = 125 °C	10	μs
T _j			-55 ... 150	°C
Inverse diode				
I _F	T _j = 150 °C	T _c = 25 °C	288	A
		T _c = 80 °C	195	A
I _{Fnom}			150	A
I _{FRM}	I _{FRM} = 2xI _{Fnom}		300	A
I _{FSM}	t _p = 10 ms, sin 180°, T _j = 25 °C		1200	A
T _j			-40 ... 150	°C
Module				
I _{t(RMS)}	T _{terminal} = 80 °C		600	A
T _{stg}			-40 ... 125	°C
V _{isol}	AC sinus 50Hz, t = 1 min		4000	V

Characteristics						
Symbol	Conditions		min.	typ.	max.	Unit
IGBT						
V _{CE(sat)}	I _C = 150 A	T _j = 25 °C		2	2.45	V
	V _{GE} = 15 V chiplevel	T _j = 125 °C		2.4	2.9	V
V _{CE0}		T _j = 25 °C		1	1.2	V
		T _j = 125 °C		0.9	1.1	V
r _{CE}	V _{GE} = 15 V	T _j = 25 °C		6.7	8.3	mΩ
		T _j = 125 °C		10.3	12.0	mΩ
V _{GE(th)}	V _{GE} =V _{CE} , I _C = 6 mA		5.2	5.8	6.4	V
I _{CES}	V _{GE} = 0 V	T _j = 25 °C			3	mA
	V _{CE} = 1700 V	T _j = 125 °C				mA
C _{ies}	V _{CE} = 25 V V _{GE} = 0 V	f = 1 MHz		13.3		nF
C _{oes}		f = 1 MHz		0.55		nF
C _{res}		f = 1 MHz		0.44		nF
Q _G	V _{GE} = - 8 V...+ 15 V			1400		nC
R _{Gint}	T _j = 25 °C			4.25		Ω
t _{d(on)}	V _{CC} = 1200 V	T _j = 125 °C		265		ns
t _r	I _C = 150 A	T _j = 125 °C		55		ns
E _{on}	V _{GE} = ±15 V	T _j = 125 °C		90		mJ
t _{d(off)}	R _{G on} = 9 Ω	T _j = 125 °C		875		ns
t _f	R _{G off} = 9 Ω	T _j = 125 °C		125		ns
E _{off}		T _j = 125 °C		55		mJ
R _{th(j-c)}	per IGBT				0.12	K/W

SEMiX252GB176HDs



SEMiX® 2s

Trench IGBT Modules

SEMiX252GB176HDs


Features

- Homogeneous Si
- Trench = Trenchgate technology
- $V_{CE(sat)}$ with positive temperature coefficient
- UL recognised file no. E63532

Typical Applications*

- AC inverter drives
- UPS
- Electronic welders

Characteristics						
Symbol	Conditions		min.	typ.	max.	Unit
Inverse diode						
V _F = V _{EC}	I _F = 150 A V _{GE} = 0 V chip	T _J = 25 °C		1.6	1.75	V
		T _J = 125 °C		1.5	1.7	V
V _{F0}		T _J = 25 °C	0.9	1.1	1.3	V
		T _J = 125 °C	0.7	0.9	1.1	V
r _F		T _J = 25 °C	3.0	3.0	3.0	mΩ
		T _J = 125 °C	4.0	4.0	4.0	mΩ
I _{RRM}	I _F = 150 A	T _J = 125 °C	205			A
Q _{rr}	di/dt _{off} = 3300 A/μs	T _J = 125 °C	55			μC
E _{rr}	V _{GE} = -15 V	T _J = 125 °C	32			mJ
	V _{CC} = 1200 V					
R _{th(j-c)}	per diode		0.19			K/W
Module						
L _{CE}			18			nH
R _{CC'+EE'}	res., terminal-chip	T _C = 25 °C	0.7			mΩ
		T _C = 125 °C	1			mΩ
R _{th(c-s)}	per module		0.045			K/W
M _s	to heat sink (M5)		3	5		Nm
M _t		to terminals (M6)	2.5	5		Nm
						Nm
w			250			g
Temperatur Sensor						
R ₁₀₀	T _C =100°C (R ₂₅ =5 kΩ)		493 ± 5%			Ω
B _{100/125}	R(T)=R ₁₀₀ exp[B _{100/125} (1/T-1/T ₁₀₀)]; T[K];		3550 ±2%			K






Fig. 1: Typ. output characteristic, inclusive $R_{CC'} + EE'$




Fig. 2: Rated current vs. temperature $I_C = f(T_C)$




Fig. 3: Typ. turn-on /-off energy = $f(I_C)$




Fig. 4: Typ. turn-on /-off energy = $f(R_G)$




Fig. 5: Typ. transfer characteristic











Fig. 6: Typ. gate charge characteristic



SEMiX252GB176HDs

Case: SEMiX 2s



guide pin left
F-F (1 : 1)





	0,3	connector 1-2 / 3-4
	0,2	each connector A

general tolerance:
ISO 2768-m
ISO 8015

screw duct (4x)
spring duct (12x):
G-G (1 : 1)



All measures in Z-direction
valid when mounted to heat sink



*guide pin left with


	$\varnothing$ 0,25	A	B	C
	$\varnothing$ 0,5	A	D	C

Rules for the contact PCB:

- holes guidepins = $\varnothing 4 \pm 0,1$ / position tolerance $\pm 0,1$
- holes for screws = $\varnothing 3,3 \pm 0,1$ / position tolerance $\pm 0,1$
- spring contact pad = $\varnothing 3,6 \pm 0,1$ / position tolerance $\pm 0,1$

**screw ducts / spring ducts / guide pin right with

SEMiX 2s



spring configuration

This is an electrostatic discharge sensitive device (ESDS), international standard IEC 60747-1, Chapter IX

* The specifications of our components may not be considered as an assurance of component characteristics. Components have to be tested for the respective application. Adjustments may be necessary. The use of SEMIKRON products in life support appliances and systems is subject to prior specification and written approval by SEMIKRON. We therefore strongly recommend prior consultation of our staff.