

SKT 10,3 Qu RG bond.



THYRISTOR

$$I_{T(DC)} = 125 \text{ A}$$

$$V_{RRM} = 1600 \text{ V}$$

Size: 10,3 mm x 10,3 mm

Corner gate

SKT 10,3 Qu RG bond.

Features

- high current density due to double mesa technology
- high surge current
- compatible to thick wire bonding
- compatible to all standard solder processes

Typical Applications*

- controlled rectifier circuits
- solid state relays

Absolute Maximum Ratings

Symbol	Conditions	Values	Unit
V_{RRM}	$T_j = 25 \text{ °C}$, $I_R = 0.2 \text{ mA}$	1600	V
V_{DRM}	$T_j = 25 \text{ °C}$, $I_D = 0.2 \text{ mA}$	1600	V
$I_{T(AV)}$	$T_c = 80 \text{ °C}$, $T_j = 130 \text{ °C}$	95	A
I_{TSM}	$T_j = 130 \text{ °C}$, 10 ms, sin 180°	1250	A
i^2t	$T_j = 130 \text{ °C}$, 10 ms, sin 180°	7810	A ² s
T_{jmax}		130	°C

Electrical Characteristics

Symbol	Conditions	min.	typ.	max.	Unit
V_T	$T_j = 130 \text{ °C}$, $I_T = 110 \text{ A}$			1.2	V
$V_{T(TO)}$	$T_j = 130 \text{ °C}$			0.85	V
r_T	$T_j = 130 \text{ °C}$			3.2	mΩ
I_{GT}	$T_j = 25 \text{ °C}$			100	mA
V_{GT}	$T_j = 25 \text{ °C}$			1.98	V
I_{GD}	$T_j = 115 \text{ °C}$	6			mA
V_{GD}	$T_j = 130 \text{ °C}$	0.25			V
I_H	$T_j = 25 \text{ °C}$			220	mA
I_L	$T_j = 25 \text{ °C}$			550	mA

Dynamic Characteristics


Symbol	Conditions	min.	typ.	max.	Unit
t_q	$T_j = 130 \text{ °C}$		150		μs
$(di/dt)_{cr}$	$T_j = 130 \text{ °C}$			100	A/μs
$(dv/dt)_{cr}$	$T_j = 130 \text{ °C}$			1000	V/μs

Thermal Characteristics


Symbol	Conditions	min.	typ.	max.	Unit
T_j		-40		130	°C
T_{stg}		-40		130	°C
T_{solder}				255	°C
$R_{th(j-c)}$	Semipack 1 assembly		0.31		K/W

Mechanical Characteristics

Symbol	Conditions	Values	Unit
Raster size		10.3 x 10.3	mm ²
Area total		106.1	mm ²
Anode		solderable (Ag/Ni)	
Gate and Cathode		bondable (Al)	
Wire bond		Al, diameter ≤ 500μm	
Package		tray	
Chips / Package		49	pcs



SKT



This is an electrostatic discharge sensitive device (ESDS), international standard IEC 60747-1, Chapter IX

* The specifications of our components may not be considered as an assurance of component characteristics. Components have to be tested for the respective application. Adjustments may be necessary. The use of SEMIKRON products in life support appliances and systems is subject to prior specification and written approval by SEMIKRON. We therefore strongly recommend prior consultation of our personal.