


SKS 275N W3C 240 V16 SU



Thyristor Stud stack

SEMISTACK® CLASSICS - W3C

Three phase reverse parallel thyristor converter

Preliminary Data

Ordering No. 08785215
Description SKS 275N W3C 240 V16 SU

Features

- Non-isolated power stacks
- SKT 300/16
- Heatsink P1/200
- Natural cooling
- RC circuit included
- Fuses with microswitches

Typical Applications

- Soft starters

Remarks


This technical information specifies semiconductor devices but promises no characteristics. No warranty or guarantee, expressed or implied, is made regarding delivery, performance or suitability.

Electrical Characteristics						
Symbol	Conditions		min	typ	max	Unit
Electrical Data						
I _{OUT}	Maximum output current	T _{AMBIENT} = 35°C ; No overload		275		A _{RMS}
V _{AC}	Maximum AC voltage (+/-10%)			500		V _{AC}
P _{TOTAL}	Maximum stack power			240		kW
P _{LOSS}	Stack power loss (T _{AMBIENT} = 35°C)					W


Environmental Data						
Symbol	Conditions		min	typ	max	Unit
Mechanical Data						
Drawing	SEMIKRON document number.revision.version		12051002.01.B		-	
Weight	Approximate total weight		20.1		kg	
Altitude	Installation altitude without derating				1 000	m
Protection	IEC 60529		IP00		-	
Pollution Degree	EN 50178		2		-	

Stack Protection						
Symbol	Conditions		min	typ	max	Unit
RC Circuit						
Type	RC in parallel with each switch		RC25B			-
R	Resistance (10W)		68			Ohm
C			0.1			μF

Fuses			
Size	1 fuse per phase, with microswitches	30	-
$I_{N RMS}$	Caliber	400	A
U_N	Nominal voltage (IEC)	690	V
I^2t	Total at U_N at room temperature (approx. 20...25°C)	126	kA^2s



W3C



Dimensions

This technical information specifies semiconductor devices but promises no characteristics. No warranty or guarantee expressed or implied is made regarding delivery, performance or suitability.