



CKE Part Number	Max. DC Voltage	Max. clamping Voltage	Fig.	Dim. A (inches)	Thread size
Series K – 3" x 3"					
SD1622-4	90	240	67	2.5000	3/8-16
SD1623-5	112	300	68	2.8750	3/8-16
SD1623-6	135	360	68	3.2500	3/8-16
SD1623-7	157	420	68	3.5000	3/8-16
SD1623-8	180	480	68	3.9375	3/8-16
SD1623-9	202	540	68	4.2500	3/8-16
SD1623-10	225	600	68	4.6250	3/8-16
SD1623-11	247	660	68	5.0000	3/8-16
SD1623-12	270	720	68	5.3125	3/8-16
SD1623-13	292	780	68	5.6875	3/8-16
SD1623-14	315	840	68	6.0000	3/8-16
SD1623-15	337	900	68	6.3750	3/8-16
SD1623-16	360	960	68	6.6875	3/8-16
SD1623-17	382	1020	68	7.0000	3/8-16
SD1623-18	405	1080	68	7.3750	3/8-16
SD1623-19	427	1140	68	7.7500	3/8-16
SD1623-20	450	1200	68	8.0625	3/8-16
SD1623-21	472	1260	68	8.4375	3/8-16
SD1623-22	495	1320	68	8.7500	3/8-16
SD1623-23	517	1380	68	9.1250	3/8-16
SD1623-24	540	1440	68	9.5000	3/8-16
SD1623-25	562	1500	68	9.8750	3/8-16
SD1623-26	585	1560	68	10.1875	3/8-16
SD1623-27	607	1620	68	10.5000	3/8-16
SD1623-28	630	1680	68	10.8750	3/8-16
SD1623-29	652	1720	68	11.2500	3/8-16
SD1623-30	675	1800	68	11.6250	3/8-16

Peak discharge current - 37 Amps

Series M – 4" x 4"					
SD1598-4	90	240	67	2.6875	3/8-16
SD1599-5	112	300	68	3.1875	3/8-16
SD1599-6	135	360	68	3.5625	3/8-16
SD1599-7	157	420	68	4.0000	3/8-16
SD1599-8	180	480	68	4.3750	3/8-16
SD1599-9	202	540	68	4.8125	3/8-16
SD1599-10	225	600	68	5.2500	3/8-16
SD1599-11	247	660	68	5.6250	3/8-16
SD1599-12	270	720	68	6.0625	3/8-16
SD1599-13	292	780	68	6.5000	3/8-16
SD1599-14	315	840	68	6.9375	3/8-16
SD1599-15	337	900	68	7.3750	3/8-16
SD1599-16	360	960	68	7.8125	3/8-16
SD1599-17	382	1020	68	8.2500	3/8-16
SD1599-18	405	1080	68	8.6250	3/8-16
SD1599-19	427	1140	68	9.0625	3/8-16
SD1599-20	450	1200	68	9.4375	3/8-16
SD1599-21	472	1260	68	9.8750	3/8-16
SD1599-22	495	1320	68	10.3125	3/8-16
SD1599-23	517	1380	68	10.6250	3/8-16
SD1599-24	540	1440	68	11.0000	3/8-16
SD1599-25	562	1500	68	11.4375	3/8-16
SD1599-26	585	1560	68	11.8750	3/8-16
SD1599-27	607	1620	68	12.2500	3/8-16
SD1599-28	630	1680	68	12.6250	3/8-16
SD1599-29	652	1720	68	13.0625	3/8-16
SD1599-30	675	1800	68	13.5000	3/8-16

Peak discharge current - 70 Amps

Series S – 5" x 6"					
SD1772-4	90	240	67	2.8750	3/8-16
SD1772-5	112	300	68	3.2500	3/8-16
SD1772-6	135	360	68	3.6250	3/8-16
SD1772-7	157	420	68	4.1250	3/8-16
SD1772-8	180	480	68	4.5000	3/8-16
SD1772-9	202	540	68	4.8750	3/8-16
SD1772-10	225	600	68	5.3750	3/8-16
SD1772-11	247	660	68	5.7500	3/8-16
SD1772-12	270	720	68	6.1250	3/8-16
SD1772-13	292	780	68	6.6250	3/8-16
SD1772-14	315	840	68	7.0000	3/8-16
SD1772-15	337	900	68	7.3750	3/8-16
SD1772-16	360	960	68	7.7500	3/8-16
SD1772-17	382	1020	68	8.2500	3/8-16
SD1772-18	405	1080	68	8.6250	3/8-16
SD1772-19	427	1140	68	9.0000	3/8-16
SD1772-20	450	1200	68	9.5000	3/8-16
SD1772-21	472	1260	68	9.8750	3/8-16
SD1772-22	495	1320	68	10.2500	3/8-16
SD1772-23	517	1380	68	10.6250	3/8-16
SD1772-24	540	1440	68	11.0000	3/8-16
SD1772-25	562	1500	68	11.5000	3/8-16
SD1772-26	585	1560	68	11.8750	3/8-16
SD1772-27	607	1620	68	12.2500	3/8-16
SD1772-28	630	1680	68	12.7500	3/8-16
SD1772-29	652	1720	68	13.1250	3/8-16
SD1772-30	675	1800	68	13.5000	3/8-16

Peak discharge current - amperes 130

Series N – 6" x 7 1/4"					
SD2482-4	90	240	67	2.8750	3/8-16
SD2482-5	112	300	68	3.2500	3/8-16
SD2482-6	135	360	68	3.6250	3/8-16
SD2482-7	157	420	68	4.1250	3/8-16
SD2482-8	180	480	68	4.5000	3/8-16
SD2482-9	202	540	68	4.8750	3/8-16
SD2482-10	225	600	68	5.3750	3/8-16
SD2482-11	247	660	68	5.7500	3/8-16
SD2482-12	270	720	68	6.1250	3/8-16
SD2482-13	292	780	68	6.6250	3/8-16
SD2482-14	315	840	68	7.0000	3/8-16
SD2482-15	337	900	68	7.3750	3/8-16
SD2482-16	360	960	68	7.7500	3/8-16
SD2482-17	382	1020	68	8.2500	3/8-16
SD2482-18	405	1080	68	8.6250	3/8-16
SD2482-19	427	1140	68	9.0000	3/8-16
SD2482-20	450	1200	68	9.5000	3/8-16
SD2482-21	472	1260	68	9.8750	3/8-16
SD2482-22	495	1320	68	10.2500	3/8-16
SD2482-23	517	1380	68	10.6250	3/8-16
SD2482-24	540	1440	68	11.0000	3/8-16
SD2482-25	562	1500	68	11.5000	3/8-16
SD2482-26	585	1560	68	11.8750	3/8-16
SD2482-27	607	1620	68	12.2500	3/8-16
SD2482-28	630	1680	68	12.7500	3/8-16
SD2482-29	652	1720	68	13.1250	3/8-16
SD2482-30	675	1800	68	13.5000	3/8-16

Peak discharge current - 200 Amps



Nonpolarized versions available. Please consult factory.