



Product Specifications

PART NO: **VL493T5269A-F7S/E7S/E6S**

REV: **1.1**

General Information

4GB 512Mx72 DDR2 SDRAM ECC REGISTERED SO-RDIMM 200-PIN WITH THERMAL SENSOR

Description The VL493T5269A is a 512Mx72 Double Data Rate DDR2 SDRAM high density SO-RDIMM. This memory module is dual rank, consists of nine stacked CMOS 512Mx8 bit with 8 banks DDR2 Synchronous DRAMs in BGA packages, a 28-bit registered buffer in BGA package, a zero delay PLL clock in BGA package, and a 2K EEPROM with thermal sensor in an 8-pin MLF package. This module is a 200-pin registered small-outline dual in-line memory module and is intended for mounting into an edge connector socket. Decoupling capacitors are mounted on the printed circuit board for each DDR2 SDRAM.

Features

- 200-pin, registered small-outline dual in-line memory module (SO-RDIMM)
- Fast data transfer rates: PC2-6400 & PC2-5300
- Supports ECC error detection and correction
- VDD = VDDQ = 1.8V
- VDDSPD = 3.0V to 3.6V
- JEDEC standard 1.8V I/O (SSTL_18 compatible)
- Differential data strobe (DQS, DQS#) option
- Differential clock inputs (CK, CK#)
- Four-bit pre-fetch architecture
- DLL aligns DQ and DQS transition with CK
- Programmable CAS# latency (CL): 5 (DDR2-800), 6 (DDR2-800) & 5 (DDR2-667)
- Write latency = Read latency - 1tCK
- Eight internal component banks for concurrent operation
- Programmable burst; length (4, 8)
- Adjustable data-output drive strength
- On-die termination (ODT)
- Auto & self refresh, (8K/64ms refresh)
- Serial presence detect (SPD) with EEPROM built-in thermal sensor
- Thermal sensor range: -20°C to +125°C (+/- 1°C Accuracy)
- Gold edge contacts
- Lead-free RoHS
- PCB: Height 30.00mm (1.181"), double sided components
- JEDEC pin out

Pin Name	Function
A0~A14	Address Inputs
BA0~BA2	Bank Address Inputs
DQ0~DQ63	Data Input/Output
CB0~CB7	Check Bits
DQS0~DQS8	Data Strobes
DQS0#~DQS8#	Data Strobes Complement
ODT0,ODT1	On-die Termination Control
CK,CK#	Clock Input
CKE0,CKE1	Clock Enables
CS0#, CS1#	Chip Selects
RAS#	Row Address Strobes
CAS#	Column Address Strobes
WE#	Write Enable
RESET#	Register Reset Input
DM0~DM8	Data Masks
VDD	Voltage Supply 1.8V +/- 0.1V
A10/AP	Address Input/Auto Precharge
VDDSPD	SPD Voltage Supply 3.0V to 3.6V
VSS	Ground
SA0~SA1	SPD Address
SDA	SPD Data Input/Output
SCL	SPD Clock Input
VREF	SSTL_18 Reference Voltage
NC	No Connect

Order Information

VL493T5269A-F7 S X

DRAM DIE (Option)

DRAM MANUFACTURER
S - SAMSUNG

MODULE SPEED
F7: PC2-6400 @ CL5
E7: PC2-6400 @ CL6
E6: PC2-5300 @ CL5

VL: Lead-free/RoHS



Product Specifications

PART NO:

VL493T5269A-F7S/E7S/E6S

REV: 1.1

Pin Configuration

200-PIN DDR2 SO-RDIMM FRONT								200-PIN DDR2 SO-RDIMM BACK							
Pin	Name	Pin	Name	Pin	Name	Pin	Name	Pin	Name	Pin	Name	Pin	Name	Pin	Name
1	VREF	51	DQ18	101	VDD	151	VSS	2	VSS	52	VSS	102	A6	152	VSS
3	DQ0	53	DQ19	103	A5	153	DQS5#	4	DQ4	54	DQ28	104	A4	154	DM5
5	VSS	55	VSS	105	A3	155	DQS5	6	DQ5	56	DQ29	106	VDD	156	VSS
7	DQ1	57	DQ24	107	A2	157	VSS	8	VSS	58	VSS	108	A1	158	DQ46
9	DQS0#	59	DQ25	109	VDD	159	DQ42	10	DM0	60	DM3	110	A0	160	DQ47
11	DQS0	61	VSS	111	A10/AP	161	DQ43	12	VSS	62	VSS	112	BA1	162	VSS
13	VSS	63	DQS3#	113	BA0	163	VSS	14	DQ6	64	DQ30	114	VDD	164	DQ52
15	DQ2	65	DQS3	115	RAS#	165	DQ48	16	DQ7	66	DQ31	116	WE#	166	DQ53
17	DQ3	67	VSS	117	VDD	167	DQ49	18	VSS	68	VSS	118	CS0#	168	VSS
19	VSS	69	DQ26	119	CAS#	169	VSS	20	DQ12	70	CB4	120	ODT0	170	DM6
21	DQ8	71	DQ27	121	CS1#	171	DQS6#	22	DQ13	72	CB5	122	A13	172	VSS
23	DQ9	73	VSS	123	VDD	173	DQS6	24	VSS	74	VSS	124	VDD	174	DQ54
25	VSS	75	CB0	125	ODT1	175	VSS	26	DM1	76	DM8	126	CK	176	DQ55
27	DQS1#	77	CB1	127	NC/CS3#	177	DQ50	28	VSS	78	VSS	128	CK#	178	VSS
29	DQS1	79	VSS	129	DQ32	179	DQ51	30	DQ14	80	CB6	130	VSS	180	DQ60
31	VSS	81	DQS8#	131	VSS	181	VSS	32	DQ15	82	CB7	132	DQ36	182	DQ61
33	DQ10	83	DQS8	133	DQ33	183	DQ56	34	VSS	84	VSS	134	DQ37	184	VSS
35	DQ11	85	VSS	135	DQS4#	185	DQ57	36	DQ20	86	CB2	136	VSS	186	DM7
37	VSS	87	CKE0	137	DQS4	187	VSS	38	DQ21	88	CB3	138	DM4	188	DQ62
39	DQ16	89	CKE1	139	VSS	189	DQS7#	40	VSS	90	VSS	140	VSS	190	VSS
41	DQ17	91	NC/CS2#	141	DQ34	191	DQS7	42	RESET#	92	BA2	142	DQ38	192	DQ63
43	VSS	93	VDD	143	DQ35	193	DQ58	44	DM2	94	A14	144	DQ39	194	SDA
45	DQS2#	95	A12	145	VSS	195	VSS	46	VSS	96	A11	146	VSS	196	SCL
47	DQS2	97	A9	147	DQ40	197	DQ59	48	DQ22	98	VDD	148	DQ44	198	SA1
49	VSS	99	A7	149	DQ41	199	VDDSPD	50	DQ23	100	A8	150	DQ45	200	SA0

Note:

1. RESET (pin 42) RESET is connected to both OE of the PLL and Reset of the register
2. CS2#, CS3# (pin 91, 127) are used for 4 rank modules




Product Specifications

PART NO:

VL493T5269A-F7S/E7S/E6S

REV: 1.1

Functional Block Diagram





Product Specifications

PART NO:

VL493T5269A-F7S/E7S/E6S

REV: 1.1

Absolute Maximum Ratings

Symbol	Parameter		MIN	MAX	Unit
V _{DD}	Voltage on V _{DD} pin relative to V _{SS}		-1.0	2.3	V
V _{DDQ}	Voltage on V _{DDQ} pin relative to V _{SS}		-0.5	2.3	V
V _{DDL}	Voltage on V _{DDL} pin relative to V _{SS}		-0.5	2.3	V
V _{IN} , V _{OUT}	Voltage on any pin relative to V _{SS}		-0.5	2.3	V
T _{STG}	Storage temperature		-55	100	°C
I _L	Input leakage current; Any input 0V<V _{IN} <V _{DD} ; VREF input 0V<V _{IN} <0.95V; Other pins not under test = 0V	Command/Address, RAS#, CAS#, WE#, CKE, ODT, BA	-5	5	μA
		CS#	-5	5	μA
		CK, CK#	-10	10	μA
		DM	-10	10	μA
I _{OZ}	Output leakage current; 0V<V _{OUT} <V _{DDQ} ; DQs and ODT are disabled	DQ, DQS, DQS#	-10	10	μA
I _{VREF}	VREF leakage current; VREF = Valid VREF level		-36	36	μA

DC Operating Conditions

All voltages referenced to V_{SS}

Parameter	Symbol	Min	Typical	Max	Unit	Notes
Supply voltage	V _{DD}	1.7	1.8	1.9	V	1
I/O Supply voltage	V _{DDQ}	1.7	1.8	1.9	V	4
VDDL Supply voltage	V _{DDL}	1.7	1.8	1.9	V	4
I/O Reference voltage	V _{REF}	0.49 x V _{DDQ}	0.50 x V _{DDQ}	0.51 x V _{DDQ}	V	2
I/O Termination voltage	V _{TT}	V _{REF} -0.04	V _{REF}	V _{REF} +0.04	V	3

- Notes: 1. V_{DD}, V_{DDQ} must track each other. V_{DDQ} must be less than or equal to V_{DD}.
2. V_{REF} is expected to equal V_{DDQ}/2 of the transmitting device and to track variations in the DC level of the same. Peak-to-peak noise on V_{REF} may not exceed +/-1percent of the DC value. Peak-to-peak AC noise on V_{REF} may not exceed +/-2 percent of V_{REF}. This measurement is to be taken at the nearest V_{REF} bypass capacitor.
3. V_{TT} is not applied directly to the device. V_{TT} is a system supply for signal termination resistors, is expected to be set equal to V_{REF} and must track variations in the DC level of V_{REF}.
4. V_{DDQ} tracks with V_{DD}; V_{DDL} tracks with V_{DD}.



Product Specifications

PART NO: VL493T5269A-F7S/E7S/E6S

REV: 1.1

Operating Temperature Condition

Parameter	Symbol	Rating	Units	Notes
Operating temperature	TOPER	0 to 95	°C	1,2

Notes:

1. Operating temperature is the case surface temperature on the center/top side of the DRAM. For the measurement conditions, please refer to JEDEC JESD51.2
2. At 0 - 85°C, operation temperature range, all DRAM specifications will be supported. The refresh rate is required to double when 85 °C < TOPER <= 95 °C

Input DC Logic Level

All voltages referenced to VSS

Parameter	Symbol	Min	Max	Unit
Input High (Logic 1) Voltage	VIH(DC)	VREF + 0.125	VDDQ + 0.300	V
Input Low (Logic 0) Voltage	VIL(DC)	-0.300	VREF - 0.125	V

Input AC Logic Level

All voltages referenced to VSS

Parameter	Symbol	Min	Max	Unit
AC Input High (Logic 1) Voltage DDR2-667 & DDR2-800	VIH(AC)	VREF + 0.200	-	V
AC Input Low (Logic 0) Voltage DDR2-667 & DDR2-800	VIL(AC)	-	VREF - 0.200	V

Input/Output Capacitance

TA=25°C, f=100MHz

Parameter	Symbol	Min	Max	Unit
Input capacitance (A0~A14, BA0~BA2, RAS#, CAS#, WE#)	CIN1	6.5	7.5	pF
Input capacitance (CKE0, CKE1), (ODT0, ODT1)	CIN2	6.5	7.5	pF
Input capacitance (CS0#~CS1#)	CIN3	6.5	7.5	pF
Input capacitance (CK, CK#)	CIN4	6	7	pF
Input/Output capacitance (DQ, DQS, DQS#, DM, CB)	CIO	9	11	pF



Product Specifications

PART NO:

VL493T5269A-F7S/E7S/E6S

REV: 1.1

IDD Specification

IDD Specification						
Condition		Symbol	F7 (DDR2-800)	E7 (DDR2-800)	E6 (DDR2-667)	Unit
Operating one bank active-precharge; $t_{CK}=t_{CK(DD)}; t_{RC}=t_{RC(DD)}; t_{RAS}=t_{RAS MIN(DD)};$ CKE is HIGH, CS# is HIGH between valid commands; Address bus inputs are SWITCHING; Data bus inputs are SWITCHING		IDD0*	1290	1290	1245	mA
Operating one bank active-read-precharge; IOUT = 0mA; BL = 4; CL = CL(IDD); $t_{CK}=t_{CK(DD)}; t_{RC}=t_{RC(DD)}; t_{RAS}=t_{RAS MIN(DD)};$ CKE is HIGH, CS# is HIGH between valid commands; Address bus inputs are SWITCHING; Data bus inputs are SWITCHING; Data pattern is same as IDD4W.		IDD1*	1515	1515	1425	mA
Precharge power-down current; All banks idle; $t_{CK}=t_{CK(DD)};$ CKE is LOW; Other control and address bus inputs are STABLE; Data bus inputs are FLOATING		IDD2P**	570	570	570	mA
Precharge quiet standby current; All banks idle; $t_{CK}=t_{CK(DD)};$ CKE is HIGH; CS# is HIGH; Other control and address bus inputs are STABLE; Data bus inputs are FLOATING		IDD2Q**	1290	1290	1200	mA
Precharge standby current; All banks idle; $t_{CK}=t_{CK(DD)};$ CKE is HIGH; CS# is HIGH; Other control and address bus inputs are STABLE; Data bus inputs are SWITCHING.		IDD2N**	1380	1380	1290	mA
Active power-down current; All banks open; $t_{CK}=t_{CK(DD)};$ CKE is LOW; Other control and address bus inputs are STABLE; Data bus inputs are FLOATING.	Fast PDN Exit MRS(12) = 0	IDD3P**	1200	1200	1020	mA
	Slow PDN Exit MRS(12) = 1		624	624	624	mA
Active standby current; All banks open; $t_{CK}=t_{CK(DD)}; t_{RC}=t_{RC(DD)}; t_{RAS}=t_{RAS MIN(DD)};$ CKE is HIGH, CS# is HIGH between valid commands; Other control and address bus inputs are SWITCHING; Data bus inputs are SWITCHING.		IDD3N**	1740	1740	1560	mA
Operating burst write current; All banks open; Continuous burst writes; BL = 4; CL = CL(IDD); AL = 0; $t_{CK}=t_{CK(DD)};$ $t_{RAS}=t_{RAS MAX(DD)}; t_{RP}=t_{RP(DD)};$ CKE is HIGH, CS# is HIGH between valid commands; Address bus inputs are SWITCHING; Data bus inputs are SWITCHING.		IDD4W*	1965	1965	1785	mA
Operating burst read current; All banks open; Continuous burst reads; IOUT = 0mA; BL = 4; CL = CL(IDD); AL = 0; $t_{CK}=t_{CK(DD)}; t_{RAS}=t_{RAS MAX(DD)}; t_{RP}=t_{RP(DD)};$ CKE is HIGH, CS# is HIGH between valid commands; Address bus inputs are SWITCHING; Data pattern is same as IDD4W.		IDD4R*	2235	2235	1965	mA
Burst auto refresh current; $t_{CK}=t_{CK(DD)};$ Refresh command at every $t_{RFC(DD)}$ interval; CKE is HIGH; CS# is HIGH between valid commands; Other control and address bus inputs are SWITCHING; Data bus inputs are SWITCHING.		IDD5**	5340	5340	4980	mA
Self refresh current; CK and CK# at 0V; CKE < 0.2V; Other control and address bus inputs are FLOATING; Data bus inputs are FLOATING.	Normal	IDD6**	270	270	270	mA
Operating bank interleave read current; All bank interleaving reads; IOUT = 0mA; BL = 4; CL = CL(IDD); AL = $t_{RCD(DD)} - 1 * t_{CK(DD)};$ $t_{CK}=t_{CK(DD)}; t_{RC}=t_{RC(DD)}; t_{RRD}=t_{RRD(DD)}; t_{RCD}=1 * t_{CK(DD)};$ CKE is HIGH; CS# is HIGH between valid commands; Address bus inputs are STABLE during DESELECTs; Data bus inputs are SWITCHING.		IDD7*	3585	3585	3315	mA

Notes: IDD specification is based on Samsung 2Gb A-die components.
*: Value calculated as one module rank in this operating condition, and all other module ranks in IDD2 (CKE LOW) mode.
**: Value calculated reflects all module ranks in this operating condition.



Product Specifications

PART NO:

VL493T5269A-F7S/E7S/E6S

REV: 1.1

AC Timing Parameters & Specifications

Parameter			Symbol	F7 (DDR2-800)		E7 (DDR2-800)		E6 (DDR2-667)		Unit
				Min	Max	Min	Max	Min	Max	
Clock	Clock cycle time	CL=6	$t_{CK}(6)$	-	-	2500	8000	-	-	ps
		CL=5	$t_{CK}(5)$	2500	8000	-	-	3000	8000	ps
	CK high-level width		t_{CH}	0.48	0.52	0.48	0.52	0.45	0.55	t_{CK}
	CK low-level width		t_{CL}	0.48	0.52	0.48	0.52	0.45	0.55	t_{CK}
	Half clock period		t_{HP}	MIN (t_{CH}, t_{CL})		MIN (t_{CH}, t_{CL})		MIN (t_{CH}, t_{CL})		ps
	Clock jitter		t_{JIT}	-100	100	-100	100	-125	125	ps
Data	DQ output access time from CK/CK#		t_{AC}	-400	400	-400	400	-450	+450	ps
	Data-out high impedance window from CK/CK#		t_{HZ}		$t_{AC}(MAX)$		$t_{AC}(MAX)$		$t_{AC}(MAX)$	ps
	Data-out low-impedance window from CK/CK#		t_{LZ}	$t_{AC}(MIN)$	$t_{AC}(MAX)$	$t_{AC}(MIN)$	$t_{AC}(MAX)$	$t_{AC}(MIN)$	$t_{AC}(MAX)$	ps
	DQ and DM input setup time relative to DQS		t_{DS}	50		50		100		
	DQ and DM input hold time relative to DQS		t_{DH}	125		125		175		
	DQ and DM input pulse width (for each input)		t_{DIPW}	0.35		0.35		0.35		t_{CK}
	Data hold skew factor		t_{QHS}		300		300		340	ps
	DQ-DQS hold, DQS to first DQ to go nonvalid, per access		t_{QH}	$t_{HP} - t_{QHS}$		$t_{HP} - t_{QHS}$		$t_{HP} - t_{QHS}$		ps
	Data valid output window (DVW)		t_{DVW}	$t_{QH} - t_{DQSQ}$		$t_{QH} - t_{DQSQ}$		$t_{QH} - t_{DQSQ}$		ns
Data Strobe	DQS input high pulse width		t_{DQSH}	0.35		0.35		0.35		t_{CK}
	DQS input low pulse width		t_{DQSL}	0.35		0.35		0.35		t_{CK}
	DQS output access time from CK/CK#		t_{DQSK}	-350	350	-350	350	-400	+400	ps
	DQS falling edge to CK rising – setup time		t_{DSS}	0.2		0.2		0.2		t_{CK}
	DQS falling edge from CK rising – hold time		t_{DSH}	0.2		0.2		0.2		t_{CK}
	DQS-DQ skew, DQS to last DQ valid, per group, per access		t_{DQSQ}		200		200		240	ps
	DQS read preamble		t_{RPRE}	0.9	1.1	0.9	1.1	0.9	1.1	t_{CK}
	DQS read postamble		t_{RPST}	0.4	0.6	0.4	0.6	0.4	0.6	t_{CK}
	DQS write preamble setup time		t_{WPRES}	0		0		0		ps
	DQS write preamble		t_{WPRE}	0.35		0.35		0.35		t_{CK}
	DQS write postamble		t_{WPST}	0.4	0.6	0.4	0.6	0.4	0.6	t_{CK}
	Write command to first DQS latching transition		t_{DQSS}	WL-0.25	WL+0.25	WL-0.25	WL+0.25	WL-0.25	WL+0.25	t_{CK}



Product Specifications

PART NO:

VL493T5269A-F7S/E7S/E6S

REV: 1.1

AC Timing Parameters & Specifications (cont')


	Parameter	Symbol	F7 (DDR2-800)		E7 (DDR2-800)		E6 (DDR2-667)		Unit
			Min	Max	Min	Max	Min	Max	
Command and Address	Address and control input pulse width for each input	t_{IPW}	0.6		0.6		0.6		t_{CK}
	Address and control input setup time	t_{IS}	175		175		200		ps
	Address and control input hold time	t_{IH}	250		250		275		ps
	CAS# to CAS# command delay	t_{CCD}	2		2		2		ps
	ACTIVE to ACTIVE (same bank) command	t_{RC}	60		60		60		ns
	ACTIVE bank a to ACTIVE bank b command	t_{RRD}	7.5		7.5		7.5		ns
	ACTIVE to READ or WRITE delay	t_{RCD}	12.5		15		15		ns
	Four Bank Activate period	t_{FAW}	37.5		37.5		37.5		ns
	ACTIVE to PRECHARGE command	t_{RAS}	45	70,000	45	70,000	45	70,000	ns
	Internal READ to precharge command delay	t_{RTP}	7.5		7.5		7.5		ns
	Write recovery time	t_{WR}	15		15		15		ns
	Auto precharge write recovery + precharge time	t_{DAL}	$t_{WR}+t_{RP}$		$t_{WR}+t_{RP}$		$t_{WR}+t_{RP}$		ns
	Internal WRITE to READ command delay	t_{WTR}	7.5		10		7.5		ns
	PRECHARGE command period	t_{RP}	12.5		15		15		ns
	PRECHARGE ALL command period	t_{RPA}	$t_{RP}+t_{CK}$		$t_{RP}+t_{CK}$		$t_{RP}+t_{CK}$		ns
	LOAD MODE command cycle time	t_{MRD}	2		2		2		t_{CK}
Self Refresh	CKE low to CK,CK# uncertainty	t_{DELAY}	$t_{IS}+t_{CK}+t_{IH}$		$t_{IS}+t_{CK}+t_{IH}$		$t_{IS}+t_{CK}+t_{IH}$		ns
	REFRESH to Active or Refresh to Refresh command interval	t_{RFC}	197.5	70,000	197.5	70,000	197.5	70,000	ns
	Average periodic refresh interval	t_{REFI}		7.8		7.8		7.8	us
	Exit self refresh to non-READ command	t_{XSNR}	$t_{RFC(MIN)}+10$		$t_{RFC(MIN)}+10$		$t_{RFC(MIN)}+10$		ns
	Exit self refresh to READ	t_{XSRD}	200		200		200		t_{CK}
ODT	Exit self refresh timing reference	t_{ISXR}	t_{IS}		t_{IS}		t_{IS}		ps
	ODT turn-on delay	t_{AOND}	2		2		2		t_{CK}
	ODT turn-on	t_{AON}	$t_{AC(MIN)}$	$t_{AC(MAX)}+700$	$t_{AC(MIN)}$	$t_{AC(MAX)}+700$	$t_{AC(MIN)}$	$t_{AC(MAX)}+700$	ps
	ODT turn-off delay	t_{AOFD}	2.5	2.5	2.5	2.5	2.5	2.5	t_{CK}
	ODT turn-off	t_{AOF}	$t_{AC(MIN)}$	$t_{AC(MAX)}+600$	$t_{AC(MIN)}$	$t_{AC(MAX)}+600$	$t_{AC(MIN)}$	$t_{AC(MAX)}+600$	ps
	ODT turn-on (power-down mode)	t_{AONPD}	$t_{AC(MIN)}+2000$	$2 \times t_{CK} + t_{AC(MAX)}+1000$	$t_{AC(MIN)}+2000$	$2 \times t_{CK} + t_{AC(MAX)}+1000$	$t_{AC(MIN)}+2000$	$2 \times t_{CK} + t_{AC(MAX)}+1000$	ps
	ODT turn-off (power-down mode)	t_{AOFPD}	$t_{AC(MIN)}+2000$	$2.5 \times t_{CK} + t_{AC(MAX)}+1000$	$t_{AC(MIN)}+2000$	$2.5 \times t_{CK} + t_{AC(MAX)}+1000$	$t_{AC(MIN)}+2000$	$2.5 \times t_{CK} + t_{AC(MAX)}+1000$	ps
	ODT to power-down entry latency	t_{ANPD}	3		3		3		t_{CK}
	ODT power-down exit latency	t_{AXPD}	10		10		8		t_{CK}
Power-Down	Exit active power-down to READ command, MR[bit12=0]	t_{XARD}	2		2		2		t_{CK}
	Exit active power-down to READ command, MR[bit12=1]	t_{XARDS}	8-AL		8-AL		7-AL		t_{CK}
	Exit precharge power-down to any non-READ command.	t_{XP}	2		2		2		t_{CK}
	CKE minimum high/low time	t_{CKE}	3		3		3		t_{CK}

Product Specifications

 PART NO: **VL493T5269A-F7S/E7S/E6S**

 REV: **1.1**

Package Dimensions



NOTE:

All dimensions are in millimeters with tolerance +/- 0.15mm unless otherwise specified.



Product Specifications

PART NO:

VL493T5269A-F7S/E7S/E6S

REV: 1.1

Revision History:

Date	Rev.	Page	Changes
06/30/2009	1.0	All	Spec release
12/14/2010	1.1	1	Update General information