



AL125ULE

Two (2) Output Switching Power Supply/Charger

Rev. DSAL125ULE - 11072012



AL125ULE

Overview

AL125ULE is a Two (2) Output Switching Power Supply/Charger that converts a 24VAC @ 40VA input, into two (2) individually PTC protected 12VDC or 24VDC outputs.

Specifications

Input:

- 24VAC, 40VA from UL Listed, Class 2 transformer.
- Access control trigger input.

Output:

- 12VDC or 24VDC selectable outputs.
- 0.5 amp supply current.
- Two (2) Class 2 Rated power limited outputs.
 - Fail-Safe/Fail-Secure lock output (switched).
 - Auxiliary power output (unswitched).
- PTC protected outputs, rated @ 2.5 amp.
- Filtered and electronically regulated output.
- Short circuit and thermal overload protection.

Battery Backup:

- Built-in charger for sealed lead acid or gel type batteries.
- Automatic switch over to stand-by battery when AC fails.
- Maximum charge current 0.4 amp.

Supervision:

- AC fail supervision (form "C" contacts).

Supervision (cont'd):

- Supervised Fire Alarm Disconnect (Latching w/reset or Non-Latching).

Visual Indicators:

- AC power and unit status indicator on the front panel.

Electrical:

- Operating temperature: 0° C to 49° C ambient.
- 3.07 or 6.14 BTU/Hr.
- System AC input VA requirement: 55.2VA.

Features:

- Includes power supply, enclosure and battery leads.

Mechanical:

- Enclosure Dimensions (H x W x D approx.):
 - 8.5" (215.9mm) x 7.5" (190.5mm) x 3.5" (88.9mm).
 - Accommodates up to two (2) 12VDC/4AH batteries or one (1) 12VDC/7AH battery.
- Product weight (approx.): 3.3 lbs. (1.50 kg).
- Shipping weight (approx.): 3.8 lbs. (1.72 kg).

Agency Approvals



UL Listed for Access Control System Units (UL 294).



CUL Listed - CSA Standard C22.2 No.1-98, Audio, Video and Similar Equipment.

Enclosure Dimensions (H x W x D) (approximate):

8.5" (215.9mm) x 7.5" (190.5mm) x 3.5" (88.9mm)

