



AL168300CBM

### **Overview**

AL168300CBM Power Supply provides 16VAC or 18VAC distributed via eight (8) PTC protected outputs for powering multiple security system or access control panels.

### **Specifications**

**Input:**

- Input 115VAC, 50/60Hz, 2.7 amp.

**Output:**

- Eight (8) PTC protected outputs.
- 16VAC or 18VAC output.
- 16VAC @ 18 amp (300VA) supply current (2.25 amp per device, 2.5 amp max.) or 18VAC @ 16 amp (300VA) supply current (2 amp per device, 2.5 amp max.).
- Outputs are rated @ 2.5 amp.
- Main fuse rated @ 10 amp/250V.
- Surge suppression.

**Visual Indicators:**

- AC power LED indicators.

**Electrical:**

- Operating temperature: 0° C to 49° C ambient.
- BTU/Hr.:
  - 16VAC: 327.57 BTU/Hr.
  - 18VAC: 331.66 BTU/Hr.
- System AC input VA requirement: 310.5VA.

**Features:**

- Illuminated master power disconnect circuit breaker with manual reset.

**Mechanical:**

- Enclosure Dimensions (H x W x D approx.): 8.5" (215.9mm) x 7.5" (190.5mm) x 3.75" (95.25mm)
- Product weight (approx.): 12.45 lbs. (5.65 kg).
- Shipping weight (approx.): 13.05 lbs. (5.92 kg).

### **Agency Approvals**



European Conformity

**Enclosure Dimensions (H x W x D) (approximate):**  
 8.5" (215.9mm) x 7.5" (190.5mm) x 3.75" (95.25mm)

