

**Overview**

AL176ULX is a Single Output Power Supply/Charger that converts a 115VAC 50/60Hz input into a PTC protected 12VDC or 24VDC output.

Specifications***Input:***

- Input 115VAC/60Hz, 0.6 amp.

Output:

- 12VDC or 24VDC selectable output.
- 1.75 amp supply current.
- Class 2 Rated power limited output.
- PTC protected outputs, rated @ 2.5 amp.
- Filtered and electronically regulated output.
- Short circuit and thermal overload protection.

Battery Backup:

- Built-in charger for sealed lead acid or gel type batteries.
- Automatic switch over to stand-by battery when AC fails.
- Maximum charge current 0.4 amp.

Supervision:

- AC fail supervision (form "C" contacts).
- Low battery supervision (form "C" contacts).

Visual Indicators:

- AC input and DC output LED indicators.

Electrical:

- Operating temperature: 0° C to 49° C ambient.
- 8-16 BTU/Hr.
- System AC input VA requirement: 69VA.

Mechanical:

- Enclosure Dimensions (H x W x D approx.):
13.5" (342.9mm) x 13" (330.2mm) x 3.25" (82.55mm)
- Accommodates up to two (2) 12VDC/7AH batteries.
- Product weight (approx.): 9.5 lbs. (4.31 kg).
- Shipping weight (approx.): 10.4 lbs. (4.72 kg).

Agency Approvals

UL Listed for Access Control System Units
(UL 294).



CUL Listed - CSA Standard C22.2 No.1-98,
Audio, Video and Similar Equipment.

Enclosure Dimensions (H x W x D) (approximate):

13.5" (342.9mm) x 13" (330.2mm) x 3.25" (82.55mm)

