



AL400UL

Overview

AL400UL is a power supply/charger that converts a 115VAC/60Hz input into a single 12VDC or 24VDC Class 2 Rated power-limited output.

Specifications

Input:

- Input 115VAC, 60Hz, 3.5 amp.

Output:

- 12VDC or 24VDC selectable output.
- 12VDC @ 4 amp or 24VDC @ 3 amp supply current.
- Class 2 Rated power-limited output.
- Filtered and electronically regulated output.
- Short circuit and thermal overload protection.

Battery Backup:

- Built-in charger for sealed lead acid or gel type batteries.
- Automatic switch over to stand-by battery when AC fails.
- Maximum charge current 1.2 amp.

Supervision:

- AC fail supervision (form “C” contacts).
- Low battery supervision (form “C” contacts).

Visual Indicators:

- AC input and DC output LED indicators.

Electrical:

- Operating temperature: 0° C to 49° C ambient.
- 24.57 or 36.85 BTU/Hr.
- System AC input VA requirement: 402.5VA.

Mechanical:

- Enclosure Dimensions (H x W x D approx.): 12.25” (311.15mm) x 7.25” (184.15mm) x 4.5” (114.3mm)
- Product weight (approx.): 8.5 lbs. (3.86 kg).
- Shipping weight (approx.): 9.4 lbs. (4.26 kg).

Agency Approvals



- UL 294 UL Listed for Access Control System Units.
- UL 603 UL Listed Standard for Power Supplies for Use with Burglar-Alarm Systems.
- UL 1481 UL Listed Standard for Safety for Fire Protective Signaling Systems.

MEA
Approved

MEA - NYC Department of Buildings Approved.



CSFM - California State Fire Marshal Approved.

Enclosure Dimensions (H x W x D) (approximate):
 12.25" (311.15mm) x 7.25" (184.15mm) x 4.5" (114.3mm)

