



AL400ULXR

**Overview**

AL400ULXR is a power supply/charger that converts a 115VAC/60Hz input into a single 12VDC or 24VDC Class 2 Rated power-limited output.

**Specifications*****Input:***

- Input 115VAC, 60Hz, 3.5 amp.
- Input fuse rated @ 3.5 amp/250V.

***Output:***

- 12VDC or 24VDC selectable output.  
Burglar Alarm Applications (UL 603):  
12VDC = 11.5VDC-13VDC.  
24VDC = 23VDC-26VDC.
- 12VDC @ 4 amp or 24VDC @ 3 amp supply current.
- Class 2 Rated power-limited output.
- Filtered and electronically regulated output.
- Short circuit and thermal overload protection.

***Battery Backup:***

- Built-in charger for sealed lead acid or gel type batteries.
- Automatic switch over to stand-by battery when AC fails.
- Maximum charge current 0.7 amp.

***Supervision:***

- AC fail supervision (form “C” contacts).
- Low battery supervision (form “C” contacts).
- Battery presence supervision (form “C” contacts).

***Visual Indicators:***

- AC input and DC output LED indicators.

***Electrical:***

- Operating temperature: 0° C to 49° C ambient.
- BTU/Hr. :  
12VDC: 14.71 - 16.63 BTU/Hr.  
24VDC: 29.43 - 32.41 BTU/Hr.
- System AC input VA requirement: 345VA.

***Mechanical:***

- Enclosure Dimensions (H x W x D approx.):  
13.5” (342.9mm) x 13” (330.2mm) x 3.25” (82.55mm)  
- Accommodates up to two (2)12VDC/7AH batteries.
- Product weight (approx.): 8.65 lbs. (3.86 kg).
- Shipping weight (approx.): 9.55 lbs. (4.26 kg).

**Agency Approvals**

- UL 294 UL Listed for Access Control System Units.
- UL 603 UL Listed Standard for Power Supplies for Use with Burglar-Alarm Systems.
- UL 1069 UL Listed Hospital Signaling and Nurse Call Equipment.
- UL 1481 UL Listed Standard for Safety for Fire Protective Signaling Systems.

**Enclosure Dimensions (H x W x D) (approximate):**

13.5" (342.9mm) x 13" (330.2mm) x 3.25" (82.55mm)

