



ALTV2416ULI UL Listed AC Isolated CCTV Power Supply

Rev. DSALTV2416ULI_12192012



ALTV2416ULHI

Overview

ALTV2416ULI Isolated CCTV Power Supply provides 24VAC distributed via sixteen (16) isolated fuse protected power limited outputs for powering CCTV Cameras, heaters and other video accessories.

Specifications

Input:

- 115VAC, 50/60Hz, 6 amp.

Output:

- Sixteen (16) fuse protected outputs.
- 24VAC @ 25 amp (600VA) supply current.
- Outputs are rated @ 3.5 amp.
- Surge suppression.

Electrical:

- Operating temperature: 0° C to 49° C ambient.
- 304.12 BTU/Hr.
- System AC input VA requirement: 690VA.

Features:

- Illuminated master power disconnect circuit breaker with manual reset.
- Unit maintains camera synchronization.
- Spare fuses provided.

Mechanical:

- Enclosure Dimensions (H x W x D approx.): 13.5" (342.9mm) x 13" (330.2mm) x 3.25" (82.55mm).
- Product weight (approx.): 23.3 lbs. (10.57 kg).
- Shipping weight (approx.): 24.3 lbs. (11.02 kg).

Agency Approvals



UL Listed for Commercial CCTV Equipment (UL 2044).



CUL Listed - CSA Standard C22.2 No.1-98, Audio, Video and Similar Equipment.



European Conformity

Enclosure Dimensions (H x W x D) (approximate):
13.5" (342.9mm) x 13" (330.2mm) x 3.25" (82.55mm)

