



ALTV2416ULCBI3 UL Listed AC Isolated CCTV Power Supply

Rev. DSALTV2416ULCBI3_12192012



ALTV248ULCBI3

Overview

ALTV2416ULCBI3 Isolated CCTV Power Supply provides 24VAC distributed via sixteen (16) isolated Class 2 Rated PTC protected power limited outputs for powering CCTV Cameras, heaters and other video accessories.

Specifications

Input:

- 115VAC, 50/60Hz, 6 amp.

Output:

- Sixteen (16) Class 2 Rated PTC protected outputs.
- 24VAC @ 25 amp (600VA) supply current.
- Outputs are rated @ 2.5 amp.
- Surge suppression.

Electrical:

- Operating temperature: 0° C to 49° C ambient.
- 304.12 BTU/Hr.
- System AC input VA requirement: 690VA.

Features:

- Illuminated master power disconnect circuit breaker with manual reset.
- Unit maintains camera synchronization.
- Spare fuses provided.
- Factory installed 3-wire line cord.

Mechanical:

- Enclosure Dimensions (H x W x D approx.): 13.5" (342.9mm) x 13" (330.2mm) x 3.25" (82.55mm).
- Product weight (approx.): 23.6 lbs. (10.71 kg).
- Shipping weight (approx.): 24.6 lbs. (11.16 kg).

Agency Approvals



UL Listed for Commercial CCTV Equipment (UL 2044).



CUL Listed - CSA Standard C22.2 No.1-98, Audio, Video and Similar Equipment.



European Conformity

Enclosure Dimensions (H x W x D) (approximate):
 13.5" (342.9mm) x 13" (330.2mm) x 3.25" (82.55mm)

