



ALTV2416ULCBX

**Overview**

ALTV2416ULCBX provides 24VAC or 28VAC distributed via Sixteen (16) Class 2 Rated PTC protected outputs for powering CCTV Cameras, heaters and other video accessories.

**Specifications*****Input:***

- 115VAC, 50/60Hz, 1.8 amp.

***Output:***

- Sixteen (16) Class 2 Rated PTC protected outputs.
- 24VAC @ 7 amp (170VA) supply current  
(0.438 amp per device, 2.5 amp max.)  
or 28VAC @ 6 amp (170VA) supply current  
(0.375 amp per device, 2.5 amp max.).
- Outputs are rated @ 2.5 amp.
- Surge suppression.

***Electrical:***

- Operating temperature: 0° C to 49° C ambient.
- BTU/Hr.: 85.99 BTU/Hr.
- System AC input VA requirement: 207VA.

***Features:***

- Secondary fuse rated @ 5 amp/250V.
- AC power LED.
- Power ON/OFF switch.

***Mechanical:***

- Enclosure Dimensions (H x W x D approx.):  
13.5" (343mm) x 13" (330mm) x 3.25" (83mm)
- Product weight (approx.): 12.6 Lbs (5.715 kg).
- Shipping weight (approx.): 13.6 Lbs (6.168 kg).

**Agency Approvals**

UL Listed for Commercial CCTV Equipment  
(UL 2044).



CUL Listed - CSA Standard C22.2 No.1-98,  
Audio, Video and Similar Equipment.



European Conformity

# **Enclosure Dimensions**

**13.5" (343mm) x 13" (330mm) x 3.25" (83mm)**

