

Overview



ALTV2432300UL

ALTV2432300UL provides 24VAC or 28VAC distributed via Thirty-Two (32) fuse protected outputs for powering CCTV Cameras, heaters and other video accessories.

Specifications

Input:

- 115VAC, 50/60Hz, 2.7 amp.

Output:

- Thirty-Two (32) fuse protected outputs.
- 24VAC @ 12.5 amp (300VA) supply current (0.391 amp per device, 3.5 amp max.) or 28VAC @ 10 amp (280VA) supply current (0.313 amp per device, 3.5 amp max.).
- Outputs are rated @ 3.5 amp.
- Surge suppression.

Electrical:

- Operating temperature: 0° C to 49° C ambient.
- BTU/Hr.:
 - 24VAC: 153.54 BTU/Hr.
 - 28VAC: 143.31 BTU/Hr.

Electrical (cont'd):

- System AC input VA requirement: 310.5VA.

Features:

- Secondary fuse rated @ 10 amp/250V.
- AC power LED.
- Power ON/OFF switch.
- Spare fuses provided.
(all models w/primary and/or secondary fuses).

Mechanical:

- Enclosure Dimensions (H x W x D approx.): 13.5" (343mm) x 13" (330mm) x 3.25" (83mm)
- Product weight (approx.): 18.5 Lbs (8.391 kg)
- Shipping weight (approx.): 19.5 Lbs (8.845 kg)

Agency Approvals



UL Listed for Commercial CCTV Equipment (UL 2044).



CUL Listed - CSA Standard C22.2 No.1-98, Audio, Video and Similar Equipment.



European Conformity

Enclosure Dimensions

13.5" (343mm) x 13" (330mm) x 3.25" (83mm)

