



### **Overview**

ALTV2432350 AC Wall Mount CCTV Power Supply provides 24VAC or 28VAC distributed via Thirty-Two (32) fuse protected outputs for powering CCTV Cameras, heaters and other video accessories.

### **Specifications**

#### ***Input:***

- 115VAC, 50/60Hz, 2.7 amp.

#### ***Output:***

- Thirty-Two (32) fuse protected outputs.
- 24VAC @ 14 amp (350VA) supply current  
(0.438 amp per device, 3.5 amp max.).
- or 28VAC @ 12.5 amp (350VA) supply current  
(0.391 amp per device, 3.5 amp max.).
- Outputs are rated @ 3.5 amp.
- Surge suppression.

#### ***Electrical:***

- Operating temperature: 0° C to 49° C ambient.
- BTU/Hr.:
  - 24VAC: 171.97 BTU/Hr.
  - 28VAC: 179.14 BTU/Hr.

#### ***Electrical (cont'd):***

- System AC input VA requirement: 310.5VA.

#### ***Features:***

- Secondary fuse rated @ 10 amp/250V.
- AC power LED.
- Power ON/OFF switch.
- Spare fuses provided.  
(all models w/primary and/or secondary fuses).

#### ***Mechanical:***

- Enclosure Dimensions (H x W x D approx.):  
13.5" (343mm) x 13" (330mm) x 3.25" (83mm).
- Product weight (approx.): 15.9 Lbs (7.21 kg).
- Shipping weight (approx.): 16.9 Lbs (7.67 kg).

### **Agency Approvals**



## ***Enclosure Dimensions***

13.5" (343mm) x 13" (330mm) x 3.25" (83mm)

