



**Altronix**<sup>®</sup>

## **ALTV2432600 AC CCTV Power Supply**

Rev. DSALTV2432600\_12172012



ALTV2432600

### **Overview**

ALTV2432600 AC Wall Mount CCTV Power Supply provides 24VAC or 28VAC distributed via Thirty-Two (32) fuse protected outputs for powering CCTV Cameras, heaters and other video accessories.

### **Specifications**

#### ***Input:***

- 115VAC, 50/60Hz, 2.7 amp.

#### ***Output:***

- Thirty-Two (32) fuse protected outputs.
- 24VAC @ 28 amp (700VA) supply current  
(0.875 amp per device, 3.5 amp max.)  
or 28VAC @ 25 amp (700VA) supply current  
(0.781 amp per device, 3.5 amp max.).
- Outputs are rated @ 3.5 amp.
- Surge suppression.

#### ***Electrical:***

- Operating temperature: 0° C to 49° C ambient.
- BTU/Hr.:
  - 24VAC: 343.94 BTU/Hr.
  - 28VAC: 358.26 BTU/Hr.

#### ***Electrical (cont'd):***

- System AC input VA requirement: 310.5VA.

#### ***Features:***

- Secondary fuse rated @ 10 amp/250V.
- AC power LED.
- Power ON/OFF switch.
- Spare fuses provided.  
(all models w/primary and/or secondary fuses).

#### ***Mechanical:***

- Enclosure Dimensions (H x W x D approx.):  
13.5" (343mm) x 13" (330mm) x 3.25" (83mm)
- Product weight (approx.): 24.6 Lbs (11.16 kg)
- Shipping weight (approx.): 25.6 Lbs (11.61 kg)

### **Agency Approvals**



European Conformity

## ***Enclosure Dimensions***

13.5" (343mm) x 13" (330mm) x 3.25" (83mm)

