



ALTV2432600CB

Overview

ALTV2432600CB AC Wall Mount CCTV Power Supply provides 24VAC or 28VAC distributed via Thirty-Two (32) PTC protected outputs for powering CCTV Cameras, heaters and other video accessories.

Specifications***Input:***

- 115VAC, 50/60Hz, 2.7 amp.

Output:

- Thirty-Two (32) PTC protected outputs.
- 24VAC @ 28 amp (700VA) supply current (0.875 amp per device, 2.5 amp max.) or 28VAC @ 25 amp (700VA) supply current (0.781 amp per device, 2.5 amp max.).
- Outputs are rated @ 2.5 amp.
- Surge suppression.

Electrical:

- Operating temperature: 0° C to 49° C ambient.
- BTU/Hr.:
 - 24VAC: 343.94 BTU/Hr.
 - 28VAC: 358.28 BTU/Hr.

Electrical (cont'd):

- System AC input VA requirement: 310.5VA.

Features:

- Secondary fuse rated @ 10 amp/250V.
- AC power LED.
- Power ON/OFF switch.

Mechanical:

- Enclosure Dimensions (H x W x D approx.): 13.5" (343mm) x 13" (330mm) x 3.25" (83mm)
- Product weight (approx.): 24.6 Lbs (11.16 kg)
- Shipping weight (approx.): 25.6 Lbs (11.61 kg)

Agency Approvals

Enclosure Dimensions

13.5" (343mm) x 13" (330mm) x 3.25" (83mm)

