



ALTV2432600ULCB3

Overview

ALTV2432600ULCB3 provides 24VAC or 28VAC distributed via Thirty-Two (32) Class 2 Rated PTC protected power limited outputs for powering CCTV Cameras, heaters and other video accessories. Factory installed 3-wire line cord.

Specifications

Input:

- 115VAC, 50/60Hz, 5.4 amp.

Output:

- Thirty-Two (32) Class 2 Rated PTC protected power limited outputs .
- 24VAC @ 25 amp (600VA) supply current (0.781 amp per device, 2.5 amp max.).
- or 28VAC @ 20 amp (560VA) supply current (0.625 amp per device, 2.5 amp max.).
- Outputs are rated @ 2.5 amp.
- Surge suppression.

Electrical:

- Operating temperature: 0° C to 49° C ambient.
- BTU/Hr.:
 - 24VAC: 307.09 BTU/Hr.
 - 28VAC: 286.62 BTU/Hr.

Electrical (cont'd):

- System AC input VA requirement: 621VA.

Features:

- Secondary fuse rated @ 10 amp/250V.
- AC power LED.
- Power ON/OFF switch.
- Factory installed 3-wire line cord.

Mechanical:

- Enclosure Dimensions (H x W x D approx.): 13.5" (343mm) x 13" (330mm) x 3.25" (83mm).
- Product weight (approx.): 24.6 Lbs (11.16 kg).
- Shipping weight (approx.): 25.6 Lbs (11.61 kg).

Agency Approvals



UL Listed for Commercial CCTV Equipment (UL 2044).



European Conformity



CUL Listed - CSA Standard C22.2 No.1-98, Audio, Video and Similar Equipment.

Enclosure Dimensions

13.5" (343mm) x 13" (330mm) x 3.25" (83mm)

