



ALTV2432CB

Overview

ALTV2432CB AC Wall Mount CCTV Power Supply provides 24VAC or 28VAC distributed via Thirty-Two (32) PTC protected outputs for powering CCTV Cameras, heaters and other video accessories.

Specifications

Input:

- 115VAC, 50/60Hz, 2.9 amp.

Output:

- Thirty-Two (32) PTC protected outputs.
- 24VAC @ 8 amp (200VA) supply current
(0.25 amp per device, 2.5 amp max.)
or 28VAC @ 7 amp (200VA) supply current
(0.219 amp per device, 2.5 amp max.).
- Outputs are rated @ 2.5 amp.
- Surge suppression.

Electrical:

- Operating temperature: 0° C to 49° C ambient.
- BTU/Hr.:
 - 24VAC: 98.27 BTU/Hr.
 - 28VAC: 100.32 BTU/Hr.

Electrical (cont'd):

- System AC input VA requirement: 333.5VA.

Features:

- Secondary fuse rated @ 10 amp/250V.
- AC power LED.
- Power ON/OFF switch.

Mechanical:

- Enclosure Dimensions (H x W x D approx.):
13.5" (343mm) x 13" (330mm) x 3.25" (83mm).
- Product weight (approx.): 9.1 Lbs (4.13 kg)
- Shipping weight (approx.): 10.1 lbs. (4.58 kg).

Agency Approvals



European Conformity

Enclosure Dimensions

13.5" (343mm) x 13" (330mm) x 3.25" (83mm)

