



ALTV244

**Overview**

ALTV244 AC Wall Mount CCTV Power Supply provides 24VAC or 28VAC distributed via four (4) fuse protected outputs for powering CCTV Cameras, heaters and other video accessories.

**Specifications*****Input:***

- 115VAC, 50/60Hz, 0.9 amp.

***Output:***

- Four (4) fuse protected outputs.
- 24VAC @ 4 amp (100VA) supply current  
(1 amp per device, 3.5 amp max.)
- or 28VAC @ 3.5 amp (100VA) supply current  
(0.875 amp per device, 3.5 amp max.).
- Outputs are rated @ 3.5 amp.
- Surge suppression.

***Electrical:***

- Operating temperature: 0° C to 49° C ambient.
- BTU/Hr.:
  - 24VAC: 49.13 BTU/Hr.
  - 28VAC: 50.16 BTU/Hr.

***Electrical (cont'd):***

- System AC input VA requirement: 103.5VA.

***Features:***

- Secondary fuse rated @ 5 amp/250V.
- AC power LED.
- Power ON/OFF switch.
- Spare fuses provided.  
(all models w/primary and/or secondary fuses).

***Mechanical:***

- Enclosure Dimensions (H x W x D approx.):  
8.5" (215.9mm) x 7.5" (190.5mm) x 3.5" (88.9mm)
- Product weight (approx.): 6.2 lbs. (2.812 kg.).
- Shipping weight (approx.): 6.8 lbs. (3.084 kg.).

**Agency Approvals**

# Enclosure Dimensions

8.5" (215.9mm) x 7.5" (190.5mm) x 3.5" (88.9mm)

