



ALTV244175UL

**Overview**

ALTV244175UL AC Wall Mount CCTV Power Supply provides 24VAC or 28VAC distributed via four (4) fuse protected power limited outputs for powering CCTV Cameras, heaters and other video accessories.

**Specifications*****Input:***

- 115VAC, 50/60Hz, 2.7 amp.

***Output:***

- Four (4) fuse protected outputs.
- 24VAC @ 7 amp (170VA) supply current  
(1.75 amp per device, 3.5 amp max.)  
or 28VAC @ 6.25 amp (175VA) supply current  
(1.56 amp per device, 3.5 amp max.).
- Outputs are rated @ 3.5 amp.
- Surge suppression.

***Electrical:***

- Operating temperature: 0° C to 49° C ambient.
- BTU/Hr.:
  - 24VAC: 85.99 BTU/Hr.
  - 28VAC: 89.57 BTU/Hr.

***Electrical (cont'd):***

- System AC input VA requirement: 340.5VA.

***Features:***

- Secondary fuse rated @ 10 amp/250V.
- AC power LED.
- Power ON/OFF switch.
- Spare fuses provided.  
(all models w/primary and/or secondary fuses).

***Mechanical:***

- Enclosure Dimensions (H x W x D approx.):  
12.25" (311mm) x 7.5" (184mm) x 4.5" (114mm)
- Product weight (approx.): 10.8 Lbs (4.898 kg)
- Shipping weight (approx.): 11.8 Lbs (5.352 kg)

**Agency Approvals**

UL Listed for Commercial CCTV Equipment  
(UL 2044).



CUL Listed - CSA Standard C22.2 No.1-98,  
Audio, Video and Similar Equipment.



European Conformity

## ***Enclosure Dimensions***

12.25" (311mm) x 7.5" (184mm) x 4.5" (114mm)

