



ALTV244175UL3

**Overview**

ALTV244175UL3 AC Wall Mount CCTV Power Supply provides 24VAC or 28VAC distributed via four (4) fuse protected power limited outputs for powering CCTV Cameras, heaters and other video accessories. Factory installed 3-wire line cord.

**Specifications*****Input:***

- 115VAC, 50/60Hz, 2.7 amp.

***Output:***

- Four (4) fuse protected outputs.
- 24VAC @ 7 amp (170VA) supply current  
(1.75 amp per device, 3.5 amp max.)  
or 28VAC @ 6.25 amp (175VA) supply current  
(1.56 amp per device, 3.5 amp max.).
- Outputs are rated @ 3.5 amp.
- Surge suppression.

***Electrical:***

- Operating temperature: 0° C to 49° C ambient.
- BTU/Hr.:
  - 24VAC: 85.99 BTU/Hr.
  - 28VAC: 89.57 BTU/Hr.

***Electrical (cont'd):***

- System AC input VA requirement: 340.5VA.

***Features:***

- Secondary fuse rated @ 10 amp/250V.
- AC power LED.
- Power ON/OFF switch.
- Factory installed 3-wire line cord.
- Spare fuses provided.  
(all models w/primary and/or secondary fuses).

***Mechanical:***

- Enclosure Dimensions (H x W x D approx.):  
12.25" (311mm) x 7.5" (184mm) x 4.5" (114mm)
- Product weight (approx.): 10.8 Lbs (4.898 kg)
- Shipping weight (approx.): 11.8 Lbs (5.352 kg)

**Agency Approvals**

UL Listed for Commercial CCTV Equipment  
(UL 2044).



CUL Listed - CSA Standard C22.2 No.1-98,  
Audio, Video and Similar Equipment.



European Conformity

## **Enclosure Dimensions**

12.25" (311mm) x 7.5" (184mm) x 4.5" (114mm)

