



ALTV244CB

Overview

ALTV244CB AC Wall Mount CCTV Power Supply provides 24VAC or 28VAC distributed via four (4) PTC protected outputs for powering CCTV Cameras, heaters and other video accessories.

Specifications

Input:

- 115VAC, 50/60Hz, 0.9 amp.

Output:

- Four (4) PTC protected outputs.
- 24VAC @ 4 amp (100VA) supply current
(1 amp per device, 2.5 amp max.)
- or 28VAC @ 3.5 amp (100VA) supply current
(0.875 amp per device, 2.5 amp max.).
- Outputs are rated @ 2.5 amp.
- Surge suppression.

Electrical:

- Operating temperature: 0° C to 49° C ambient.
- BTU/Hr.:
 - 24VAC: 49.13 BTU/Hr.
 - 28VAC: 50.16 BTU/Hr.

Electrical (cont'd):

- System AC input VA requirement: 103.5VA.

Features:

- Secondary fuse rated @ 5 amp/250V.
- AC power LED.
- Power ON/OFF switch.

Mechanical:

- Enclosure Dimensions (H x W x D approx.):
8.5" (215.9mm) x 7.5" (190.5mm) x 3.5" (88.9mm)
- Product weight (approx.): 6.2 lbs. (2.812 kg).
- Shipping weight (approx.): 6.8 lbs. (3.084 kg).

Agency Approvals



Enclosure Dimensions

8.5" (215.9mm) x 7.5" (190.5mm) x 3.5" (88.9mm)

