



ALTV244ULCB

**Overview**

ALTV244ULCB AC Wall Mount CCTV Power Supply provides 24VAC or 28VAC distributed via four (4) Class 2 Rated PTC protected power limited outputs for powering CCTV Cameras, heaters and other video accessories.

**Specifications*****Input:***

- 115VAC, 50/60Hz, 0.9 amp.

***Output:***

- Four (4) PTC protected outputs.
- 24VAC @ 3.5 amp (85VA) supply current (0.875 amp per device, 2.5 amp max.) or 28VAC @ 3 amp (85VA) supply current (0.75 amp per device, 2.5 amp max.).
- Outputs are rated @ 2.5 amp.
- Surge suppression.

***Electrical:***

- Operating temperature: 0° C to 49° C ambient.

***Electrical (cont'd):***

- BTU/Hr.: 42.99 BTU/Hr.
- System AC input VA requirement: 103.5VA.

***Features:***

- Secondary fuse rated @ 5 amp/250V.
- AC power LED.
- Power ON/OFF switch.

***Mechanical:***

- Enclosure Dimensions (H x W x D approx.): 8.5" (215.9mm) x 7.5" (190.5mm) x 3.5" (88.9mm)
- Product weight (approx.): 6.4 Lbs (2.91 kg).
- Shipping weight (approx.): 7 Lbs (3.18 kg).

**Agency Approvals**

UL Listed for Commercial CCTV Equipment (UL 2044).



CUL Listed - CSA Standard C22.2 No.1-98, Audio, Video and Similar Equipment.



Canadian Standard Association



European Conformity

## Enclosure Dimensions

8.5" (215.9mm) x 7.5" (190.5mm) x 3.5" (88.9mm)

