



WPTV244175UL

**Overview**

WPTV244175UL provides power via four (4) protected outputs for CCTV cameras, heaters and other video accessories.

**Specifications****Input:**

- 115VAC, 50/60Hz, 1.76 amp.

**Output:**

- Four (4) protected outputs:
  - One (1) fuse protected non-power limited output rated at 10 amp/250VA.
  - Three (3) Class 2 Rated PTC protected power limited outputs rated @ 2.5 amp.
- 24VAC @ 7 amp (175VA) supply current or 28VAC @ 6.25 amp (175VA) supply current
- Surge suppression.

**Electrical:**

- Operating temperature: 0° C to 49° C ambient.
- BTU/Hr.: 89.57 BTU/Hr.
- System AC input VA requirement: 202.4VA.

**Features:**

- AC power LED.
- Illuminated power disconnect circuit breaker with manual reset.
- Spare fuses provided.
- NEMA 4 Rated enclosure for outdoor use.

**Mechanical:**

- Enclosure Dimensions (H x W x D approx.): 12" (305mm) x 7.75" (197mm) x 4.5" (114mm).
- Product weight (approx.): 14.75 lbs. (5.624 kg).
- Shipping weight (approx.): 16.0 lbs. (6.078 kg).

**Agency Approvals**

UL Listed for Commercial CCTV Equipment (UL 2044).



CUL Listed - CSA Standard C22.2 No.1-98, Audio, Video and Similar Equipment.



European Conformity

**PMK1 Pole Mount Kit (order separately)**

PMK1

PMK1 pole mount kit is designed to simplify installation of outdoor units.

- Accommodates 2"- 8"(diameter) poles.
- Kit includes:
  - Two (2) powder coated steel mount brackets.
  - Four (4) stainless steel bolts.
  - Four (4) stainless steel lock washers.
  - Two (2) wormgear quick release straps.

**Enclosure Dimensions (H x W x D) (approximate):**

12" (304.8mm) x 8" (203.2mm) x 6" (152.4mm)

