



ALTV248175CB

Overview

ALTV248175CB AC Wall Mount CCTV Power Supply provides 24VAC or 28VAC distributed via Eight (8) PTC protected outputs for powering CCTV Cameras, heaters and other video accessories.

Specifications***Input:***

- 115VAC, 50/60Hz, 1.5 amp.

Output:

- Eight (8) PTC protected outputs.
- 24VAC @ 7.25 amp (175VA) supply current
(0.906 amp per device, 2.5 amp max.)
or 28VAC @ 6.25 amp (175VA) supply current
(0.781 amp per device, 2.5 amp max.).
- Outputs are rated @ 2.5 amp.
- Surge suppression.

Electrical:

- Operating temperature: 0° C to 49° C ambient.
- BTU/Hr.:
 - 24VAC: 89.06 BTU/Hr.
 - 28VAC: 89.57 BTU/Hr.

Electrical (cont'd):

- System AC input VA requirement: 172.5VA.

Features:

- Secondary fuse rated @ 10 amp/250V.
- AC power LED.
- Power ON/OFF switch.

Mechanical:

- Enclosure Dimensions (H x W x D approx.):
8.5" (215.9 mm) x 7.5" (190.5 mm) x 3.5" (88.9 mm)
- Product weight (approx.): 8.5 lbs. (3.855 kg).
- Shipping weight (approx.): 9.5 lbs. (4.309 kg).

Enclosure Dimensions

8.5" (215.9mm) x 7.5" (190.5mm) x 3.5" (88.9mm)

