



ALTV248175ULCB

**Overview**

ALTV248175ULCB provides 24VAC or 28VAC distributed via Eight (8) Class 2 Rated PTC protected power limited outputs for powering CCTV Cameras, heaters and other video accessories.

**Specifications*****Input:***

- 115VAC, 50/60Hz, 1.73 amp.

***Output:***

- Eight (8) Class 2 Rated PTC protected power limited outputs.
- 24VAC @ 7 amp (170VA) supply current (0.875 amp per device, 2.5 amp max.) or 28VAC @ 6.25 amp (175VA) supply current (0.781 amp per device, 2.5 amp max.).
- Outputs are rated @ 2.5 amp.
- Surge suppression.

***Electrical:***

- Operating temperature: 0° C to 49° C ambient.
- BTU/Hr.:
  - 24VAC: 85.99 BTU/Hr.
  - 28VAC: 89.57 BTU/Hr.

***Electrical (cont'd):***

- System AC input VA requirement: 198.95VA.

***Features:***

- Secondary fuse rated @ 10 amp/250V.
- AC power LED.
- Power ON/OFF switch.

***Mechanical:***

- Enclosure Dimensions (H x W x D approx.): 12.25" (311mm) x 7.25" (184mm) x 4.5" (114mm)
- Product weight (approx.): 8.5 lbs. (3.855 kg).
- Shipping weight (approx.): 9.5 lbs. (4.309 kg).

**Agency Approvals**

UL Listed for Commercial CCTV Equipment (UL 2044).



CUL Listed - CSA Standard C22.2 No.1-98, Audio, Video and Similar Equipment.



European Conformity

## Enclosure Dimensions

12.25" (311mm) x 7.25" (184mm) x 4.5" (114mm)

