



ALTV248175ULCB3

Overview

ALTV248175ULCB3 provides 24VAC or 28VAC distributed via Eight (8) Class 2 Rated PTC protected power limited outputs for powering CCTV Cameras, heaters and other video accessories. Factory installed 3-Wire line cord.

Specifications

Input:

- 115VAC, 50/60Hz, 1.73 amp.

Output:

- Eight (8) Class 2 Rated PTC protected power limited outputs.
- 24VAC @ 7 amp (170VA) supply current
(0.875 amp per device, 2.5 amp max.)
or 28VAC @ 6.25 amp (175VA) supply current
(0.781 amp per device, 2.5 amp max.).
- Outputs are rated @ 2.5 amp.
- Surge suppression.

Electrical:

- Operating temperature: 0° C to 49° C ambient.
- BTU/Hr.:
 - 24VAC: 85.99 BTU/Hr.
 - 28VAC: 89.57 BTU/Hr.

Electrical (cont'd):

- System AC input VA requirement: 198.95VA.

Features:

- Secondary fuse rated @ 10 amp/250V.
- AC power LED.
- Factory installed 3-Wire line cord.
- Power ON/OFF switch.

Mechanical:

- Enclosure Dimensions (H x W x D approx.):
12.25" (311mm) x 7.25" (184mm) x 4.5" (114mm)
- Product weight (approx.): 8.5 lbs. (3.855 kg).
- Shipping weight (approx.): 9.5 lbs. (4.309 kg).

Agency Approvals



UL Listed for Commercial CCTV Equipment
(UL 2044).



CUL Listed - CSA Standard C22.2 No.1-98,
Audio, Video and Similar Equipment.



European Conformity

Enclosure Dimensions

12.25" (311mm) x 7.25" (184mm) x 4.5" (114mm)

