



ALTV248300

Overview

ALTV248300 AC Wall Mount CCTV Power Supply provides 24VAC or 28VAC distributed via Eight (8) fuse protected outputs for powering CCTV Cameras, heaters and other video accessories.

Specifications

Input:

- 115VAC, 50/60Hz, 2.7 amp.

Output:

- Eight (8) fuse protected outputs.
- 24VAC @ 14 amp (350VA) supply current
(1.75 amp per device, 3.5 amp max.)
- or 28VAC @ 12.5 amp (350VA) supply current
(1.563 amp per device, 3.5 amp max.).
- Outputs are rated @ 3.5 amp.
- Surge suppression.

Electrical:

- Operating temperature: 0° C to 49° C ambient.
- BTU/Hr.:
 - 24VAC: 171.97 BTU/Hr.
 - 28VAC: 179.13 BTU/Hr.

Electrical (cont'd):

- System AC input VA requirement: 310.5VA.

Features:

- Secondary fuse rated @ 15 amp/32V.
- AC power LED.
- Power ON/OFF switch.
- Spare fuses provided.
(all models w/primary and/or secondary fuses).

Mechanical:

- Enclosure Dimensions (H x W x D approx.):
12.25" (311 mm) x 7.25" (184 mm) x 4.5" (114 mm).
- Product weight (approx.): 11.4 lbs. (5.17 kg).
- Shipping weight (approx.): 12.4 lbs. (5.624 kg).

Agency Approvals



European Conformity

Enclosure Dimensions

12.25" (311mm) x 7.25" (184mm) x 4.5" (114mm)

