



ALTV248300CBM

### **Overview**

ALTV248300CBM AC Wall Mount CCTV Power Supply provides 24VAC or 28VAC distributed via Eight (8) PTC protected outputs for powering CCTV Cameras, heaters and other video accessories.

### **Specifications**

**Input:**

- 115VAC 50/60Hz, 2.5 amp.

**Output:**

- Eight (8) PTC protected outputs.
- 24VAC @ 12.5 amp (300VA) supply current  
(1.56 amp per device, 2.5 amp max.)
- or 28VAC @ 10 amp (300VA) supply current  
(1.25 amp per device, 2.5 amp max.).
- Outputs are rated @ 2.5 amp.
- Surge suppression.

**Electrical:**

- Operating temperature: 0° C to 49° C ambient.
- BTU/Hr.:
  - 24VAC: 153.55 BTU/Hr.
  - 28VAC: 143.31 BTU/Hr.

**Electrical (cont'd):**

- System AC input VA requirement: 287.5VA.

**Features:**

- Secondary fuse rated @ 10 amp/250V.
- AC power LED.
- Power ON/OFF switch.

**Mechanical:**

- Enclosure Dimensions (H x W x D approx.):  
8.5" (216 mm) x 7.5" (191 mm) x 3.5" (89 mm)
- Product weight (approx.): 9.4 lbs. (4.263 kg).
- Shipping weight (approx.): 10.4 lbs. (4.717 kg).

### **Agency Approvals**



# Enclosure Dimensions

8.5" (216mm) x 7.5" (191mm) x 3.5" (89mm)

