



ALTV248300M

Overview

ALTV248300M AC Wall Mount CCTV Power Supply provides 24VAC or 28VAC distributed via Eight (8) fuse protected outputs for powering CCTV Cameras, heaters and other video accessories.

Specifications***Input:***

- 115VAC 50/60Hz, 2.7 amp.

Output:

- Eight (8) fuse protected outputs.
- 24VAC @ 12.5 amp (300VA) supply current
(1.56 amp per device, 3.5 amp max.)
or 28VAC @ 10 amp (300VA) supply current
(1.25 amp per device, 3.5 amp max.).
- Outputs are rated @ 3.5 amp.
- Surge suppression.

Electrical:

- Operating temperature: 0° C to 49° C ambient.
- BTU/Hr.:
 - 24VAC: 153.55 BTU/Hr.
 - 28VAC: 143.31 BTU/Hr.

Electrical (cont'd):

- System AC input VA requirement: 310.5VA.

Features:

- Secondary fuse rated @ 10 amp/250V.
- AC power LED.
- Power ON/OFF switch.
- Spare fuses provided.
(all models w/primary and/or secondary fuses).

Mechanical:

- Enclosure Dimensions (H x W x D approx.):
8.5" (216 mm) x 7.5" (191 mm) x 3.5" (89 mm)
- Product weight (approx.): 9.4 lbs. (4.263 kg).
- Shipping weight (approx.): 10.4 lbs. (4.717 kg).

Agency Approvals

Enclosure Dimensions

8.5" (216mm) x 7.5" (191mm) x 3.5" (89mm)

