



ALTV248300ULCBM

**Overview**

ALTV248300ULCBM provides 24VAC or 28VAC distributed via Eight (8) Class 2 Rated PTC protected power limited outputs for powering CCTV Cameras, heaters and other video accessories.

**Specifications****Input:**

- 115VAC, 50/60Hz, 2.7 amp.

**Output:**

- Eight (8) Class 2 Rated PTC protected power limited outputs.
- 24VAC @ 12.5 amp (300VA) supply current (1.563 amp per device, 2.5 amp max.) or 28VAC @ 10 amp (280VA) supply current (1.25 amp per device, 2.5 amp max.).
- Outputs are rated @ 2.5 amp.
- Surge suppression.

**Electrical:**

- Operating temperature: 0° C to 49° C ambient.
- BTU/Hr.:
  - 24VAC: 153.55 BTU/Hr.
  - 28VAC: 143.31 BTU/Hr.

**Electrical (cont'd):**

- System AC input VA requirement: 310.5VA.

**Features:**

- Secondary fuse rated @ 15 amp/32V.
- AC power LED.
- Power ON/OFF switch.

**Mechanical:**

- Enclosure Dimensions (H x W x D approx.): 8.5" (216mm) x 7.5" (191mm) x 3.5" (89mm)
- Product weight (approx.): 10.85 Lbs (4.921 kg).
- Shipping weight (approx.): 11.35 Lbs (5.148 kg).

**Agency Approvals**

UL Listed for Commercial CCTV Equipment (UL 2044).



CUL Listed - CSA Standard C22.2 No.1-98, Audio, Video and Similar Equipment.



European Conformity

# Enclosure Dimensions

8.5" (216mm) x 7.5" (191mm) x 3.5" (89mm)

