



ALTV248600UL

Overview

ALTV248600UL provides 24VAC or 28VAC distributed via Eight (8) fuse protected outputs for powering CCTV Cameras, heaters and other video accessories.

Specifications**Input:**

- 115VAC, 50/60Hz, 5.4 amp.

Output:

- Eight (8) fuse protected outputs.
- 24VAC @ 25 amp (600VA) supply current (3.125 amp per device, 3.5 amp max.) or 28VAC @ 20 amp (560VA) supply current (2.5 amp per device, 3.5 amp max.).
- Outputs are rated @ 3.5 amp.
- Surge suppression.

Electrical:

- Operating temperature: 0° C to 49° C ambient.
- BTU/Hr.:
 - 24VAC: 307.09 BTU/Hr.
 - 28VAC: 286.62 BTU/Hr.

Electrical (cont'd):

- System AC input VA requirement: 621VA.

Features:

- Secondary fuse rated @ 15 amp/32V.
- AC power LED.
- Power ON/OFF switch.
- Spare fuses provided.
(all models w/primary and/or secondary fuses).

Mechanical:

- Enclosure Dimensions (H x W x D approx.): 13.5" (343mm) x 13" (330mm) x 3.25" (83mm)
- Product weight (approx.): 22.2 Lbs (10.07 kg).
- Shipping weight (approx.): 23.2 Lbs (10.52 kg).

Agency Approvals

UL Listed for Commercial CCTV Equipment (UL 2044).



CUL Listed - CSA Standard C22.2 No.1-98, Audio, Video and Similar Equipment.



European Conformity

Enclosure Dimensions

13.5" (343mm) x 13" (330mm) x 3.25" (83mm)

