



ALTV248CBHI AC Isolated CCTV Power Supply

Rev. DSALTV248HI - 12182012



ALTV248CBHI

Overview

ALTV248CBHI Isolated CCTV Power Supply provides 24VAC distributed via eight (8) PTC protected isolated outputs for powering CCTV Cameras, heaters and other video accessories.

Input:

- 115VAC, 50/60Hz, 2.7 amp.

Output:

- Eight (8) PTC protected outputs.
- 24VAC @ 14 amp (336VA) supply current.
- Outputs are rated @ 2.5 amp.
- Surge suppression.

Electrical:

- Operating temperature: 0° C to 49° C ambient.
- 171.97 BTU/Hr.
- System AC input VA requirement: 310.5VA.

Features:

- Illuminated master power disconnect circuit breaker with manual reset.
- Spare fuses provided.

Mechanical:

- Enclosure Dimensions (H x W x D approx.): 12.25" (311.15mm) x 7.25" (184.15mm) x 4.5" (114.3mm).
- Product weight (approx.): 14.4 lbs. (6.53 kg).
- Shipping weight (approx.): 14.8 lbs. (6.71 kg).

Enclosure Dimensions (H x W x D) (approximate):

12.25" (311.15mm) x 7.25" (184.15mm) x 4.5" (114.3mm)

