



# ALTV248CBMI AC Isolated CCTV Power Supply

Rev. DSALTV248CBMI - 12182012



ALTV248CBMI

## **Overview**

ALTV248CBMI Isolated CCTV Power Supply provides 24VAC distributed via eight PTC protected isolated outputs for powering CCTV Cameras, heaters and other video accessories.

## **Specifications**

### ***Input:***

- 115VAC, 50/60Hz, 2.7 amp.

### ***Output:***

- Eight (8) PTC protected isolated outputs.
- 24VAC @ 12.5 amp (300VA) supply current.
- Outputs are rated @ 2.5 amp.
- Surge suppression.

### ***Electrical:***

- Operating temperature: 0° C to 49° C ambient.
- 153.55 BTU/Hr.
- System AC input VA requirement: 310.5VA.

### ***Features:***

- Illuminated master power disconnect circuit breaker with manual reset.
- Unit maintains camera synchronization.
- Spare fuses provided.

### ***Mechanical:***

- Enclosure Dimensions (H x W x D approx.): 8.5" (215.9mm) x 7.5" (190.5mm) x 3.5" (88.9mm).
- Product weight (approx.): 12.25 lbs. (5.56 kg).
- Shipping weight (approx.): 12.75 lbs. (5.78 kg).

**Enclosure Dimensions (H x W x D) (approximate):**

8.5" (215.9mm) x 7.5" (190.5mm) x 3.5" (88.9mm)

