



ALTV248ULMI3 UL Listed AC Isolated CCTV Power Supply

Rev. DSALTV248ULMI3_12192012



ALTV248ULMI3

Overview

ALTV248ULMI3 Isolated CCTV Power Supply provides 24VAC distributed via eight (8) isolated fuse protected power limited outputs for powering CCTV Cameras, heaters and other video accessories.

Specifications

Input:

- 115VAC, 50/60Hz, 3 amp.

Output:

- Eight (8) fuse protected outputs.
- 24VAC @ 12.5 amp (300VA) supply current.
- Outputs are rated @ 3.5 amp.
- Surge suppression.

Electrical:

- Operating temperature: 0° C to 49° C ambient.
- 153.55 BTU/Hr.
- System AC input VA requirement: 345VA.

Features:

- Illuminated master power disconnect circuit breaker with manual reset.
- Unit maintains camera synchronization.
- Spare fuses provided.
- Factory installed 3-wire line cord.

Mechanical:

- Enclosure Dimensions (H x W x D approx.): 8.5" (215.9mm) x 7.5" (190.5mm) x 3.5" (88.9mm).
- Product weight (approx.): 11.9 lbs. (5.4 kg).
- Shipping weight (approx.): 12.4 lbs. (5.62 kg).

Agency Approvals



UL Listed for Commercial CCTV Equipment (UL 2044).



CUL Listed - CSA Standard C22.2 No.1-98, Audio, Video and Similar Equipment.



European Conformity

Enclosure Dimensions (H x W x D) (approximate):

8.5" (215.9mm) x 7.5" (190.5mm) x 3.5" (88.9mm)

