



Altronix[®]

ALTV615DC1016 DC CCTV Power Supply

Rev. DSALTV615DC1016_12182012



ALTV615DC1016

Overview

ALTV615DC1016 provides 6-15VDC distributed via sixteen (16) fuse protected outputs for powering CCTV Cameras, heaters and other video accessories.

Specifications

Input:

- Input 115VAC, 50/60 Hz, 1.9 amp.

Output:

- Sixteen (16) fuse protected outputs.
- 6VDC to 15VDC field adjustable.
- 10 amp total continuous supply current
(0.625 amp per device, 3.5 amp max.).
- Output fuses are rated @ 3.5 amp/250VAC.
- Filtered and electronically regulated outputs.

Electrical:

- Operating temperature: 0° C to 49° C ambient.
- 30.71-76.77 BTU/Hr.
- System AC input VA requirement: 218.5VA.

Features:

- AC input and DC output LED indicators.
- Illuminated power disconnect circuit breaker with manual reset.
- Spare fuse(s) provided.
- Unit maintains camera synchronization.
- Ease of installation saves time and eliminates costly labor.

Mechanical:

- NEMA1 enclosure.
- Enclosure Dimensions (H x W x D approx.):
13.5" (342.9mm) x 13" (330.2mm) x 3.25" (82.55mm)
- Product weight (approx.): 14.9 lbs. (6.76 kg).
- Shipping weight (approx.): 16.2 lbs. (7.35 kg).

Enclosure Dimensions (H x W x D) (approximate):

13.5" (342.9mm) x 13" (330.2mm) x 3.25" (82.55mm)

