



### **Overview**

ALTV615DC1016CB provides 6-15VDC distributed via sixteen (16) PTC protected outputs for powering CCTV Cameras, heaters and other video accessories.

### **Specifications**

#### ***Input:***

- Input 115VAC, 50/60 Hz, 1.9 amp.

#### ***Output:***

- Sixteen (16) PTC protected outputs.
- 6VDC to 15VDC field adjustable.
- 10 amp total continuous supply current  
(0.625 amp per device, 3.5 amp max.).
- Output fuses are rated @ 2.5 amp/250VAC.
- Filtered and electronically regulated outputs.

#### ***Electrical:***

- Operating temperature: 0° C to 49° C ambient.
- 30.71-76.77 BTU/Hr.
- System AC input VA requirement: 218.5VA.

#### ***Features:***

- AC input and DC output LED indicators.
- Illuminated power disconnect circuit breaker with manual reset.
- Unit maintains camera synchronization.
- Ease of installation saves time and eliminates costly labor.

#### ***Mechanical:***

- NEMA1 enclosure.
- Enclosure Dimensions (H x W x D approx.):  
13.5" (342.9mm) x 13" (330.2mm) x 3.25" (82.55mm)
- Product weight (approx.): 14.9 lbs. (6.76 kg).
- Shipping weight (approx.): 16.2 lbs. (7.35 kg).

# **Enclosure Dimensions (H x W x D) (approximate):**

13.5" (342.9mm) x 13" (330.2mm) x 3.25" (82.55mm)

