



ALTV615DC416ULCBM UL Listed DC CCTV Power Supply

Rev. DSALTV615DC416ULCBM - 10222012



ALTV615DC416ULCBM

Overview

ALTV615DC416ULCBM provide 6VDC to 15VDC distributed via sixteen (16) Class 2 Rated PTC protected power limited outputs for powering CCTV Cameras, heaters and other video accessories.

Specifications

Input:

- Input 115VAC, 50/60 Hz, 0.9 amp.

Output:

- Sixteen (16) Class 2 Rated PTC protected power limited outputs.
- 6VDC to 15VDC field adjustable.
- 4 amp total continuous supply current (0.25 amp per device, 2.5 amp max.).
- Outputs are rated @ 2.5 amp.
- Filtered and electronically regulated outputs.

Electrical:

- Operating temperature: 0° C to 49° C ambient.
- 12.28-30.71 BTU/Hr.
- System AC input VA requirement: 103.5VA.

Features:

- AC input and DC output LED indicators.
- Illuminated power disconnect circuit breaker with manual reset.
- Unit maintains camera synchronization.
- Ease of installation saves time and eliminates costly labor.

Mechanical:

- NEMA1 enclosure.
- Enclosure Dimensions (H x W x D approx.): 8.5" (215.9mm) x 7.5" (190.5mm) x 3.75" (95.25mm)
- Product weight (approx.): 7.8 lbs. (3.54 kg.).
- Shipping weight (approx.): 8.3 lbs. (3.76 kg.).

Agency Approvals



UL Listed for Commercial CCTV Equipment (UL 2044).



cUL Listed - CSA Standard C22.2 No.1-98, Audio, Video and Similar Equipment.

Enclosure Dimensions (H x W x D) (approximate):
 8.5" (215.9mm) x 7.5" (190.5mm) x 3.75" (95.25mm)

